

March 7, 2006

Ms. Peggy Carr Sonoma County Department of Health Services 475 Aviation Boulevard, Suite 220 Santa Rosa, California 95403-2097

Subject:

Groundwater Monitoring Well and Soil Boring Installation Results Report

Rotten Robbie Service Station No. 60

55 E. Todd Road, Santa Rosa, Sonoma County, California

Apex Project No. RMA01 001

Dear Ms Carr:

Apex Envirotech, Inc. (Apex) has been authorized by Robinson Oil Corporation (Robinson) to provide this results report in response to the Sonoma County Department of Health Services (SCDHS) letter, dated May 16, 2005 regarding the above referenced site (Figure 1). A copy of the SCDHS's letter is included as Appendix A. This work was performed to characterize the extent of residual hydrocarbons in soil at the site.

This results report has been developed in part on the basis of information obtained by Apex from Robinson and the SCDHS, and is subject to modification as newly acquired information may warrant.

BACKGROUND

August 18, 2003 - RM Associates (RMA) supervised the installation of eight soil borings at the subject property as part of a Phase II Environmental Site Assessment conducted in association with the sale of the property from Mr Dave Zedrick to Robinson. RMA collected soil samples from three of the borings and groundwater samples from all eight of the borings. RMA documented the results in, *Report of Phase II Environmental Site Assessment*, dated October 13, 2003.

September 9, 2003 - The SCDHS requested a workplan to investigate the site

November 4 - 5, 2003 - Soil and pavement were excavated from above the former gasoline and diesel underground storage tanks (UST). The materials were temporarily stockpiled onsite, pending analysis and profiling. RMA sampled the stockpiled soil on November 6, 2003.

November 7, 2003 - Armer/Norman and Associates removed the five former USTs. No holes were noted in any of the USTs. Under the direction of the Sonoma County Department of Emergency Services and the SCDHS, RMA collected confirmation soil samples from the UST basin. Ecology Control Industries under Uniform Hazardous Waste Manifests hauled the USTs offsite.

November 10, 2003 - RMA collected five 4:1 composite soil samples from the stockpiled soil that had been removed from the new UST location.

December 3, 2003 - The former product lines and dispensers were removed. RMA collected confirmation samples and six 4:1 composite samples from the stockpiled soil.

January 16, 2004 - RMA documented the results of the UST removal and replacement, Report of Underground Storage Tank Removal

February 23, 2004 - Apex submitted, *Workplan for Preliminary Site Assessment*, outlining the installation and sampling of 10 direct-push soil borings and four groundwater monitoring wells. The SCDHS approved the workplan in a letter dated March 9, 2004.

June 15 - 16, 2004 - Apex supervised the installation of nine direct-push soil borings (GP-1, GP-3 through GP-10) to delineate the lateral and vertical extent of soil and groundwater contamination beneath the site. GP-1, GP-3, GP-4 and GP-6 through GP-10 were drilled to a total depth of 12 feet below ground surface (bgs), and GP-5 was drilled to a total depth of 20 feet bgs.

July 7 - July 9, 2004 - Apex personnel supervised vacuum clearing, drilling, sampling and installation of four groundwater monitoring wells (MW-1 through MW-4).

November 9, 2004 - Apex submitted the report, *Preliminary Site Assessment Results Report and Fourth Quarter 2004 Groundwater Monitoring Report*, detailing activities and results for boring and monitoring well installation activities.

December 30, 2004 - SCDHS requested a workplan to complete characterization of the site. In addition, the SCDHS requested completion of a sensitive receptor survey.

March 2, 2005 - Apex submitted the report titled, Sensitive Receptor Survey and Workplan for Additional Site Characterization, proposing the installation of three additional soil borings, and five groundwater monitoring wells to further characterize the site

April 28, 2005 - Apex submitted a "Clarification Letter" to address the concerns of the SCDHS

May 16, 2005 – Apex received a letter from the SCDHS approving the work dated March 2, 2005.

MONITORING WELL INSTALLATION ACTIVITIES

Underground Service Alert was contacted for identification of buried utilities at or entering the project site from the public right-of-way. For safety purposes, the first 5-feet of each boring was hand augured.

On October 4, 2005, Apex supervised the installation of three groundwater monitoring wells (MW-5 through MW-7) (Figure 2). The wells were installed by Woodward Drilling Co., Inc., of Rio Vista, California. Wells MW-5 through MW-7 were installed onsite in an attempt to delineate the lateral and vertical extent of petroleum hydrocarbons in soil beneath the site. Monitoring wells MW-8 and MW-9, proposed in the Caltrans right-of-way were not installed during this mobilization due to the lengthy permitting process involved in obtaining encroachment permits for these wells. Upon approval of the NCRWQCB, Apex proceeded with the installation of wells MW-5 through MW-7 and is currently awaiting the approval of encroachment permits for wells MW-8 and MW-9.

Well Construction Details

Groundwater monitoring wells MW-5 through MW-7 were installed as 2-inch diameter Schedule-40 PVC monitoring wells to a total depth of 23-feet bgs. The well casings were screened with 0.020-inch slotted screen from 3-feet bgs to total depth. All groundwater monitoring wells were constructed with #3 Monterey sand filter pack to 1-foot above the screened interval followed by one foot of bentonite seal and Portland cement to the surface. The wells are protected with locking expansion caps and flush-mounted traffic-rated vault boxes. All work was completed in accordance with the Apex standard operating procedures (SOP) included in Appendix B. Well construction details are presented in Table 1.

Soil Sampling

Soil samples were collected from each boring at five-foot intervals, and at obvious lithologic changes. As proposed in the approved workplan, a minimum of two soil samples from borings MW-5 through MW-7, were submitted to a State-certified laboratory for analysis. In order to correlate new soil analytical data with data collected during the initial subsurface investigation, the samples from the 10.5 and 15-foot bgs intervals were submitted to the laboratory, along with additional samples.

Soil lithology and visual observations for each sampled boring were recorded in the field. Soil samples were field screened with a photo ionization device. All sampling was conducted in accordance with the Apex SOP included in Appendix B. Soil encountered during the installation of the wells was logged according to the unified soil classification system, under the supervision of a State of California registered professional geologist Boring logs for each of the wells are presented as Appendix C.

DIRECT-PUSH SOIL BORING INSTALLATION ACTIVITIES

On October 6, 2005, Apex personnel supervised the advancement of three direct-push soil borings (GP-1B, GP-5B, and GP-11) (Figure 2) All direct-push soil borings were continuously sampled from surface to the top of the first aquitard. A sample of the aquitard was then collected from each boring. Boring GP-11 was also sampled at 5-, 10-, and 15-feet bgs due to the indication of possible contamination observed in the field. Total depths varied with each boring. Boring GP-1B was advanced to 28.5-feet bgs, boring GP-5B was advanced to 29-feet bgs and boring GP-11 was advance to 24-feet. The borings were then grouted to the surface using type I-II cement in accordance with SCDEH regulations.

Analytical Procedures

All soil samples were submitted under chain-of-custody (COC) documentation to California Laboratory Services of Rancho Cordova, California, a State-certified analytical laboratory. The samples were analyzed for:

Analysis	Abbreviation	Designation	USEPA Method No.			
Total Petroleum Hydrocarbons as Diesel	TPHd	Petroleum	8015M			
Total Petroleum Hydrocarbons as Gasoline	TPHg	Hydrocarbons	OU I SIVI			
Benzene						
Toluene	BTEX	Aromatic Volatile	8021B			
Ethylbenzene	DILX	Organics	00216			
Xylenes (Total)						
Methyl Tertiary Butyl Ether	MTBE					
Di-isopropyl ether	DIPE					
Ethyl tertiary-butyl ether	ETBE					
Tertiary-amyl methyl ether	TAME	Fuel Oxygenates				
Tert-butyl alcohol	TBA		8260B			
Ethanol	Ethanol					
Methanol	Methanol					
1,2-Dichloroethane	1,2-DCA	Lead				
1,2-Dibromoethane	EDB	Scavengers				

In addition to the analyses listed in the table above, a 4:1 composite soil stockpile sample was also analyzed for total lead by EPA Method 6010 for disposal purposes. Soil analytical results for the site are presented in Table 2. Copies of the laboratory results and COC documentation are presented in Appendix D. All soil and rinsate water generated during drilling activities is being stored onsite in Department of Transportation approved 55-gallon drums.

Groundwater Monitoring Well and Soil Boring Installation Results Report
Rotten Robbie Service Station No 60, 55 E. Todd Road, Santa Rosa, Sonoma County, California
Page 5

CONCLUSIONS

According to the soil analytical data from the installation of three groundwater monitoring wells, well MW-5 had detectable levels of TBA in all four samples and MTBE in sample MW-5-23'. Wells MW-6 and MW-7 were below laboratory detection limits for all analyzed constituents.

Boring GP-11 had decreasing levels of TBA. MTBE and toluene were also detected at boring GP-11. Boring GP-5B had a detection of ethylbenzene with a concentration just above the detection limit. Analytical results for GP-1B were below laboratory detection limits for all analyzed constituents.

RECOMMENDATIONS

Installation of wells MW-8 and MW-9 has been postponed until the receipt of Caltrans encroachment permits.

Apex recommends adding the three new monitoring wells to the existing sampling plan and to continue groundwater monitoring at the site to develop groundwater gradient and contaminant concentration trends. All wells (MW-1 through MW-7) will be sampled during the first quarter 2006 groundwater monitoring event, which is scheduled for March 2006.

Groundwater Monitoring Well and Soil Boring Installation Results ReportRotten Robbie Service Station No 60, 55 E Todd Road, Santa Rosa, Sonoma County, California Page 6

REPORT DISTRIBUTION

Apex submitted a copy of this report to:

Ms. Peggy Carr Sonoma County Department of Health Services 475 Aviation Boulevard, Suite 220 Santa Rosa, California 95403-2097 (707) 565-6577

Mr. Luis Rivera North Coast Regional Water Quality Control Board 5550 Skylane Boulevard, Suite A Santa Rosa, California 95403

Mr. Tom Robinson

Mr. Ron Michelson

Mr. Dave Zedrick

REMARKS/SIGNATURES

The information contained within this results report reflects our professional opinions and was developed in accordance with currently available information, and accepted hydrogeologic and engineering practices

The proposed work described above was performed under the direct supervision of the professional geologist, registered with the State of California, whose signature appears below

We appreciate the opportunity to provide Robinson with geologic, engineering and environmental consulting services, and trust this results report meets your needs. If you have any questions or comments, please call us at (916) 851-0174

SCOURANG

Sincerely,

APEX ENVIROTECH, INC.

Kelli N. Felker Project Manager


Michael Sgourakis, P.G. Senior Geologist


C.P.G. No. 7194

Groundwater Monitoring Well and Soil Boring Installation Results ReportRotten Robbie Service Station No. 60, 55 E Todd Road, Santa Rosa, Sonoma County, California Page 8


FIGURES:

FIGURE 1 SITE VICINITY MAP
FIGURE 2 SITE PLAN MAP
TABLES:
TABLE 1 WELL CONSTRUCTION DETAILS
TABLE 2 SOIL ANALYTICAL DATA
APPENDICES:
APPENDIX A SCDHS LETTER DATED MAY 16, 2005
APPENDIX B APEX STANDARD OPERATING PROCEDURES
APPENDIX C BORING LOGS AND WELL CONSTRUCTION DIAGRAMS
APPENDIX D LABORATORY ANALYTICAL REPORTS AND CHAIN OF CUSTODY FORMS





	DRAWN BY: D. Alston DATE: 2/10/04 REVISIONS	SITE VICINITY MAP	FIGURE
APEX ENVIROTECH, INC.		Rotten Robbie Service Station No 60 55 Todd Road Santa Rosa, California	PROJECT NUMBER: RMA01.001






TABLE 1 WELL CONSTRUCTION DETAILS

Rotten Robbie Service Station

55 E Todd Road Santa Rosa, California

Well Number	Well Installation Date	*Elevation TOC (feet)	Casing Material	Total Depth (feet)	Well Depth (feet)	Casing Diameter (inches)	Screened Interval (feet)	Filter Pack Interval (feet)
MW-1 MW-2 MW-3 MW-4 MW-5 MW-6 MW-7	7/9/2004 7/8/2004 7/8/2004 7/8/2004 10/4/2005 10/4/2005 10/4/2005	104.67 104.15 104.87 105.94 104.27 105.85 104.15	PVC PVC PVC PVC PVC PVC	23 23 23 23 23 23 23 23	23 23 23 23 23 23 23 23	6 4 4 2 2 2 2	3-23 3-23 3-23 3-23 3-23 3-23 3-23	2-23 2-23 2-23 2-23 2-23 2-23 2-23

Notes:

* = Surveyed by Apex Envirotech Inc to mean sea level

TOC = Top of Casing

PVC = Polyvinyl Chloride

SOIL ANALYTICAL DATA Rotten Robbie Service Station 55 E. Todd Road Santa Rosa, California **TABLE 2**

F			7	7				··	_				····							_			
	769		(ma/ka)			ł		}	;	1	-		I		ŧ				!	ļ	;	4.3	
	12 DCA	4	(ug/kg)	, v	2 4	, v	0.00	? ?	\$20 \$20	<5.0	<5.0	\$20	<5.0	<5.0	<5.0	<5.0	Ċ.	9 4	9 4	?	<5.0	<5.0	
	EDB)	(ug/kg)	۶) ų	9 4	9 6	?	<5.0	\$50	\$	\$5.0	<5.0	<5.0	<5.0	<5.0	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	, v	5 4	7 1	0.6	<5.0	
	Methanol		(mg/kg)	<5.0	, i	7 7	92.0	2	0. 0.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	5.5), A) (0.6>	<5.0	
	Ethanol		(mg/kg)	<5.0	, r	9 4	\$ \$) (0.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	λ 5 (5)	9 4	0.0°	<5.0	
afoc	TBA		(ug/kg)	1.300	10 000	400	420		S V	V20	\$	Ç20	99	25	× 20	\$0	28.000	25,000	540	3	ŧ.	1,700	
Filel Oxygenates	TAME		(ug/kg)	<5.0	0.50	5.5	\$ 650	Ļ	0.05	<5.0	<5.0	<5.0	<5.0	~ 5.0	<5.0	<5.0	<5.0	<5.0	5.0	1	0.00	€0.0	_
ű	MTBE		(ug/kg)	<5.0	<5.0	55.0	860	Ų	7.0	- - - - -	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	37	19	<5.0	200	7007	5.1	
	ETBE		(ug/kg)	<5.0	\$50	\$20	<5.0 <5.0		9	0. V2.0	Q.9	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	2,7	?	<5.0	
	DIPE		(ug/kg)	<5.0	<5.0	\$20	\$20	, ,	7	0.0 V	<5.0	\$20	<5.0	<5.0	<5.0	<5.0	<5.0	€5.0	<5.0	رج د	?	<5.0	
TICS	Total	Xylenes	(ug/kg)	<10	×10	×10	49	7	7	0L>	₽	×10	<10	₽	<10	<10	710	۲ <u>۰</u>	<u>۱</u>	4	?	<10	
latile Organics		Benzene	(ug/kg)	<5.0	<5.0	<5.0	<5.0		3 4	0.0	0.5 25.0	\$20 \$20	<5.0	V20	<5.0	5.4	<5.0	<5.0	<5.0	\ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	}	<5.0	
Aromatic Volati	Toluene		(ug/kg)	<5.0	<5.0	<5.0	0.5		, i	0.0 -	V2.0	€.0	<5.0	<5.0 <5.0	<5.0	<5.0	<5.0	5.9	<5.0	\$5.0	9	<5.0	
A	Benzene	_	(ug/kg)	<5.0	\$50	<5.0	2 0.0	\$5.0	e e	0.0	0.5 -	V250	<5.0	0.6 	<5.0	<5.0	<5.0	<5.0	<5.0	<5.0	}	<5.0	
TPH as	Diesel		(mg/kg)	41.0	0. 7.0	<1.0	v.1.0	\$5.0	7	7 1	<1.0	√ 7.0	0.12	0.1^	۸ 0.	<1.0	<1.0	۸. ۲.0	0.1.0	0.10	!	۸۲.0	***
TPH as	Gasoline		(ug/kg)	<1,000	√1,000 √1,000	<1,000	000,1	<1.000	5	000	000,	000,1	<1,000	000'1	<1,000	<1,000	<1,000	<1,000	×1,000	×1,000		<1,000	
Date of	Sampling			10/4/2005	10/4/2005	10/4/2005	10/4/2005	10/4/2005	10/4/2005	10/4/2005	C002/4/01	10/4/2005	10/4/2005	10/4/2003	10/6/2005	10/6/2005	10/6/2005	10/6/2005	10/6/2005	10/6/2005	· 	10/6/2005	
Sample	_			MW-5-6'	MW-5-10.5	MW-5-15	MW-5-23	MW-6-5.5'	MW-6-10 5	MANA CARE	MVV-0-10.0	MVV-6-23.5	MW-7-10.5	C'C1-1-AAIAI	GP-1B-25	GP-5B-27.5	GP-11-5	GP-11-10	GP-11-15	GP-11-21.5"		SP-1	

Notes:

TPH - Total Petroleum Hydrocarbons MTBE - Methyl Tertiary Butyl Ether TBA - Tertiary Butyl Alcohol DIPE - Di-Isopropyl Ether ETBE - Ethyl Tertiary Butyl Ether TAME - Tertiary Amyl Methyl Ether

EDB - 1,2-Dibromoethane
1,2 DCA - 1,2-Dichloroethane
ug/kg - micrograms per kilogram
mg/kg - milligrams per kilogram
--- - not analyzed

APPENDIX A SCDHS LETTER DATED MARCH 16, 2005

Rita Scardaci, MPH – Director Sharon Aguilera – Assistant Director

Environmental Health Division

Walter L Kruse - Director

May 16, 2005

PMAOLON RECEIVED DW MAY 19 2005

David and Susan Zedrick P.O. Box 7010 Santa Rosa, CA 95407 FILE COPY

Subject: 55 Todd Road, Santa Rosa -Leaking Underground Storage Tank Site

SCDHS-EHD Site # 00025034, NCRWQCB Site # 1TSO861

Sensitive Receptor Survey and Workplan for Additional Site Characterization Report (Apex Envirotech, Inc., March 2, 2005) and Clarification Letter (April 28, 2005)

Dear Mr and Mrs Zedrick:

On March 22, 2005, this Department received the referenced report from Apex Envirotech, Inc. The document has been reviewed by our staff, which includes a Licensed Civil Engineer and we generally concur with the proposal to advance three Geoprobes and then install five monitoring wells to fully characterize the extent of contamination at the subject site. Please note the additional specific comments as follows:

- 1. An approved LUST Drilling Permit Application is required from this Department prior to the implementation of the work. An Attachment 3 Exemption form must be completed before the permit can be approved if any of the proposed monitoring wells are within 100 feet of a septic system, 50 feet of a public sewer line, or 25 feet within a private sewer line. An acceptable Site Safety Plan must be submitted for review prior to issuance of a LUST Drilling Permit and implementation of the work plan.
- 2. Drilling spoils placed on visqueen must be covered and bermed to prevent excess vapors and rainwater runoff. Drums of purge water and equipment rinsate must be clearly labeled with a description of the material drummed, source, and date of generation.
- 3. All contaminated or potentially contaminated materials generated from the investigation or cleanup of this site must be properly disposed and accounted for. Please retain all shipping documents and receipts of disposal of these materials for submittal to this Department.
- 4. 48 hour notice must be given to this Department prior to implementation of the workplan. "Stepped-out" borings may be done with verbal or written concurrence from Department staff when soils are found obviously contaminated.

David and Susan Zedrick May 16, 2005 Page 2

- 5 If groundwater is not encountered when boring to the proposed depth, the borings must be advanced until groundwater is reached or to a minimum of 50 feet if no groundwater is observed. Significant confining layers should not be penetrated.
- 6. The following data must be submitted electronically to the State Geotracker database as required by Title 23, Division 3, Chapter 30, Article 2, Sections 3890-3895 of the California Code of Regulations: 1) All chemical analytical results for soil, water and vapor samples; 2) latitudes and longitudes of any permanent sampling points; 3) surveyed elevations of permanent sampling points; 4) elevations of groundwater at permanent sampling points; 5) site map; 6) depths of screened intervals and lengths of screened intervals for any permanent sampling points; 7) boring logs (PDF format); and 8) complete copies of reports and workplans including the signed transmittal letters and professional certifications (PDF format). Information on electronic reporting can be found on the State Water Resources Control Board web page: http://www.waterboards.ca.gov/ust/cleanup/electronic_reporting/

July 15, 2005 has been established as the due date for the implementation of the work plan and the submittal of a report of findings.

The State Cleanup Fund has discontinued its preapproval process because of a staffing shortage; however, reasonable and necessary costs should be eligible for reimbursement. The site must be in compliance with this Department's directives to be eligible for funding.

Please call me at (707) 565-6575 if you have any questions.

Sincerely,

Gary Holtz Registered Environmental Health Specialist

Leaking Underground Storage Tank, Local Oversight Program

GH

c: Mr. David Charter, SWRCB Cleanup Fund

Mr. Michael Sgourakis, Apex Envirotech, Inc., 11244 Pyrites Way, Gold River, CA 95670

Mr. Luis Rivera, NCRWQCB

Mr. Ron Michelson, RM Associates, 16401 Meadow Vista Drive, Suite 102, Pioneer, CA 95666

APPENDIX B APEX STANDARD OPERATING PROCEDURES

APEX ENVIROTECH, INC.

STANDARD OPERATING PROCEDURES

SOP-1B DIRECT PUSH SOIL SAMPLING

During drilling, soil samples for chemical analysis are collected in thin-walled teflon sleeves, of varying diameters and lengths (e.g., 2 to 4 feet long by 2 inches outside diameter). A sampling sleeve is set inside the sampler of the appropriate inside-diameter. The sampler is driven hydraulically. The sampler is extracted from the borehole and the teflon sleeve, containing the soil samples, is removed.

A sample six-inches in length is sawed off from the teflon sleeve. The ends of this six-inch section are then capped with aluminum foil or "Teflon" sheets and plastic caps. To minimize the potential for cross-contamination and volatilization of volatile organic compounds (VOC) prior to chemical analysis, the sample is labeled, and sealed in a plastic bag. The sample is then placed in a cooler containing small bags of ice. The ice packs are placed around the sample to immobilize and chill it. This is all done within one minute of removal from the sampler. The cooler is kept in one location, unless travel is required for further sampling. Samples are later transported, under strict chain-of-custody, to the analytical laboratory

In some events the soil samples cannot be submitted to the analytical laboratory on the same day. In these cases the soil samples are temporarily stored until the first opportunity for submittal either on ice in a cooler, such as when in the field, or in a refrigerator at Apex's office.

For quality control purposes, a duplicate soil sample will be analyzed. The duplicate sample will be run by splitting the contents of one brass sleeve. This will be done in the laboratory, and will be requested on the COC form

One soil sample collected at each sampling interval is analyzed in the field using a portable photoionization detector (PID), flame ionization detector, organic vapor analyzer, catalytic gas detector, or an explosimeter. The purpose of this field analysis is to qualitatively determine the presence or absence of hydrocarbons. After the first sample has been sawed off for chemical analysis, another 3-inch section is removed and the material is emptied into a brass tube, glass jar, or plastic bag to allow for some volatilization of VOC. The soil is analyzed and the concentrations of hydrocarbons within the container's headspace are measured. The data is recorded on both field notes and the boring logs at the depth corresponding to the sampling point.

The teflon sleeve is then cut open and the remaining soil is classified according to the Unified Soil Classification System. The soil types are indicated on logs of either excavations or borings together with depths corresponding to the sampling points and other pertinent information. These are used to generate a stratigraphic profile beneath the project site, and estimate the relative permeability of the subsurface materials.

All drilling and sampling equipment are either steam cleaned or washed in solution and doubly rinsed in deionized water prior to use at each site and between boreholes to minimize the potential for cross-contamination.

APEX ENVIROTECH, INC.

STANDARD OPERATING PROCEDURE Monitoring Wells

SOP - 1 SOIL BORING SAMPLING

During drilling, soil samples for chemical analysis are collected in thin-walled brass tubes, of varying diameters and lengths (e.g., 4 or 8 inches long by 2 inches outside diameter). Three or four of the selected tubes, plus a spacer tube, are set in an 18-inch long split-barrel sampler of the appropriate insidediameter.

Where possible, the split-barrel sampler is driven its entire length either hydraulically or using a 140-pound drop hammer. The sampler is extracted from the borehole and the brass tubes, containing the soil samples, are removed. Upon removal from the sampler, the selected brass tubes are either immediately trimmed and capped with aluminum foil or "Teflon" sheets and plastic caps or the samples are extruded from the tubes and sealed within other appropriate, cleaned sample containers. The samples are then hermetically sealed, labeled, and refrigerated for delivery, under strict chain-of-custody, to the analytical laboratory. These procedures minimize the potential for cross-contamination and volatilization of volatile organic compounds (VOC) prior to chemical analysis.

One soil sample collected at each sampling interval is analyzed in the field using either a portable photoionization detector (PID), flame ionization detector, organic vapor analyzer, catalytic gas detector, or an explosimeter. The purpose of this field analysis is to qualitatively determine the presence or absence of hydrocarbons, and the samples to be analyzed at the laboratory. The soil sample is sealed in either a brass tube, glass jar, or plastic bag to allow for some volatilization of VOC. The PID is then used to measure the concentrations of hydrocarbons within the containers's headspace. The data is recorded on both field notes and the boring logs at the depth corresponding to the sampling point.

Other soil samples are collected to document the soil and/or stratigraphic profile beneath the project site, and estimate the relative permeability of the subsurface materials. All drilling and sampling equipment are either steam cleaned or washed in solution and doubly rinsed in deionized water prior to use at each site and between boreholes to minimize the potential for cross-contamination.

In the event the soil samples cannot be submitted to the analytical laboratory on the same day they are collected (e.g., due to weekends or holidays), the samples are temporarily stored until the first opportunity for submittal either on ice in a cooler, such as when in the field or in a refrigerator at Apex's office.

SOF - 3 SOIL CLASSIFICATION

Soil samples are classified according to the Unified Soil Classification System. Representative portions of the samples may be submitted, under strict chain-of-custody, to an analytical laboratory for further examination and verification of the In-field classification and analysis of soil mechanical and/or petrophysical properties. The soil types are indicated on logs of either excavations or borings together with depths corresponding to the sampling points and other pertinent information.

SOP - 4 SAMPLE IDENTIFICATION AND CHAINOF-CUSTODY PROCEDURES

Sample identification and chain-of-custody procedures ensure sample integrity as well as document sample possession from the time of collection to ultimate disposal. Each sample container submitted for analysis is labeled to identify the job number, date, time of sample collection, a sample number unique to the sample, any in-field measurements made, sampling methodology, name(s) of on-site personnel, and any other pertinent field observations also recorded on the field excavation or boring log.

Chain-of-custody forms are used to record possession of the sample from time of collection to arrival at the laboratory During shipment, the person with custody of the samples will relinquish them to the next person by signing the chain-of-custody form(s) and noting the date and time. The sample-control officer at the laboratory will verify sample integrity, correct preservation, confirm collection in the proper container(s), and ensure adequate volume for analysis.

If these conditions are met, the samples will be assigned unique laboratory log numbers for identification throughout analysis and reporting. The log numbers will be recorded on the chain-of-custody forms and in the legally-required log book maintained in the laboratory. The sample description, date received client's name, and any other relevant information will also be recorded.

SOP - 5 LABORATORY ANALYTICAL QUALITY ASSURANCE AND CONTROL

In addition to routine instrument calibration, replicates, spikes, blanks, spiked blanks, and certified reference materials are routinely analyzed at method-specific frequencies to monitor precision and bias. Additional components of the laboratory Quality Assurance/Quality Control program include:

- Participation in state and federal laboratory accreditation/certification programs;
- Participation in both U.S. EPA Performance Evaluation studies (WS and WP studies) and interlaboratory performance evaluation programs;
- Standard operating procedures describing routine and periodic instrument maintenance;
- "Out-of-Control"/Corrective Action documentation procedures; and,
- 5. Multi-level review of raw data and client reports.

SOP - 6 HOLLOW-STEM AUGER MONITORING WELL INSTALLATION AND DEVELOPMENT

Boreholes for monitoring wells are drilled using a truckmounted, hollow-stem auger drill rig. The borehole diameter will be a minimum of 4 inches larger than the outside diameter of the casing when installing well screen. The hollow-stem auger provides minimal interruption of drilling while permitting soil sampling at desired intervals. Soil samples are collected by either hammering (with a 140-pound drop hammer) or hydraulically pushing a conventional split-barrel sampler containing pre-cleaned 2-inch-diameter brass tubes. A geologist or engineer from Apex Envirotech, Inc., continuously logs each borehole during drilling and constantly checks drill cuttings for indications of both the first recognizable occurrence of groundwater and volatile hydrocarbons using either a portable photoionization detector, flame ionization detector, or an explosimeter. The sampler is rinsed between samples and either steam cleaned or washed with all other drilling equipment between borings to minimize the potential for cross-contamination.

Monitoring wells are cased with threaded, factory-perforated and blank Schedule 40 PVC. The perforated interval consists of slotted casing, generally with 0.020-inch wide by 1.5-inch long slots, with 42 slots per foot. A PVC cap may be secured to the bottom of the casing with stainless steel screws; no solvents or cements are used. Centering devices may be fastened to the casing to ensure even distribution of filter material and grout within the borehole annulus. The well casing is thoroughly washed and/or steam cleaned, or may be purchased as pre-cleaned, prior to installation.

After setting the casing inside the hollow-stem auger, sand or gravel fifter material is poured into the annular space to fill from boring bottom to generally 1 foct above the perforated interval. A 1- to 2-foot thick bentonite plug is set above this fifter material to prevent grout from infiftrating the fifter pack. Either neat cement, containing about 5 percent bentonite, or sand-cement grout is then tremmied into the annular space from the top of the bentonite plug to near surface. A traffic-rated vault is installed around each wellhead for wells located in parking lots or driveways, while steel "stovepipes" are usually set over wellheads in landscaped areas.

After installation, the wells are thoroughly developed to remove residual drilling materials from the wellbore, and to improve well performance by removing fine material from the filter pack that may pass into the well. Well development techniques used may include pumping, surging bailing, swabbing, jetting, flushing and air-lifting. All development water is collected either in drums or tanks for temporary storage, and properly disposed of depending on laboratory analytical results. To minimize the potential for cross-contamination between wells, all development equipment is either steam cleaned or properly washed prior to use. Following development, the well is allowed to stand undisturbed for a minimum of 24 hours before its first sampling.

SOP - 7 GROUNDWATER PURGING AND SAMPLING

Prior to water sampling, each well is purged by evacuating a minimum of three wetted well-casing volumes of groundwater. When required, purging will continue until either the discharge water temperature, conductivity, or pH stabilize, a maximum of ten wetted-casing volumes of groundwater have been recovered, or the well is bailed dry. When practical, the groundwater sample should be collected when the water level in the well recovers to at least 80 percent of its static level.

The sampling equipment consists of either a "Teflon" bailer, PVC bailer, or stainless steel bladder pump with a "Teflon" bladder. If the sampling system is dedicated to the well, then the bailer is usually "Teflon," but the bladder pump is PVC with a polypropylene bladder. In general and depending on the intended laboratory analysis, 40-milliliter glass, volatile organic

analysis (VOA) vials, with "Tellon" septa are used as sample containers.

The groundwater sample is decanted into each VOA vial in such a manner that there is no meniscus at the top of the vial. A cap is quickly secured to the top of the vial. The vial is then inverted and gently tapped to see if air bubbles are present. If none are present, the vial is labeled and refrigerated for delivery, under strict chain-of-custody, to the analytical laboratory. Label information should include a unique sample identification number, job identification number, date, time type of analysis requested, and the sampler's name

For quality control purposes, a duplicate water sample is collected from each well. This sample may also be analyzed or put on hold at the laboratory. When required, a trip blank, prepared at the laboratory, is placed in the transport cooler. It is labeled similar to the well samples, remains in the cooler during transport, and is analyzed by the laboratory along with the groundwater samples. In addition, a field blank may be prepared in the field when sampling equipment is not dedicated. The field blank is prepared after a pump or bailer has been either steam cleaned or properly washed, prior to use in the next well, and is analyzed along with the other samples. The field blank analysis demonstrates the effectiveness of the in-field cleaning procedures to prevent cross-contamination.

To minimize the potential for cross-contamination between wells, all well development and water sampling equipment not dedicated to a well is either steam cleaned or properly washed between use. As a secondary precautionary measure, wells are sampled in order of least to highest concentrations as established by available previous analytical data.

In the event the water samples cannot be submitted to the analytical laboratory on the same day they are collected (e.g., due to weekends or holidays), the samples are temporarily stored until the first opportunity for submittal either on water ice in a cooler, such as when in the field, or in refrigerator at Apex's office.

SOP - 12 MEASURING LIQUID LEVELS USING WATER LEVEL METER OR INTERFACE PROBE

Field equipment used for liquid-level gauging typically includes the measuring instrument (water-level meter or interface probe) and product bailer(s). The field kit also includes cleaning supplies (buckets, solution, spray bottles, and deionized water) to be used in cleaning the equipment between wells

Prior to measurement, the instrument tip is lowered into the well until it touches bottom. Using the previously established top-of-casing or top-of-box (i.e., wellhead vault) point, the probe cord (or halyard) is marked and a measuring tape (graduated in hundredths of a foot) is used to determine the distance between the probe end and the marking on the cord. This measurement is then recorded on the liquid-level data sheet as the "Measured Total Depth" of the well.

When necessary in using the Interface probe to measure liquid levels, the probe is first electrically grounded to either the metal stove pipe or another metal object nearby. When no ground is available, reproducible measurements can be obtained by clipping the ground lead to the handle of the interface probe case

The probe tip is then lowered into the well and submerged in the groundwater. An oscillating (beeping) tone indicates the probe is in water. The probe is slowly raised until either the oscillating tone ceases or becomes a steady tone. In either case, this is the depth-to-water (DTW) indication and the DTW measurement is made accordingly. The steady tone indicates floating liquid hydrocarbons (FLH). In this case, the probe is slowly raised until the steady tone ceases. This is the depth-to-product (DTP) indication and the DTP measurement is made accordingly.

The process of lowering and raising the probe must be repeated several times to ensure accurate measurements. The DTW and DTP measurements are recorded on the liquid-level data sheet. When FLH are indicated by the probe's response, a product bailer is lowered partially through the FLH-water interface to confirm the FLH on the water surface and as further indication of the FLH thickness, particularly in cases where the FLH layer is quite thin. This measurement is recorded on the data sheet as "FLH thickness."

In order to avoid cross-contamination of wells during the liquidlevel measurement process, wells are measured in the order of "clean" to "dirty" (where such information is available). In addition, all measurement equipment is cleaned with solution and thoroughly rinsed with deionized water before use, between measurements in respective wells and at the completion of the day's use

APPENDIX C BORING LOGS AND WELL CONSTRUCTION DIAGRAMS

	Project	R	otten Robi	bie		55	Todd	Road	BORING			MW-5	
EMMROTECH, INC.	Project:		e Station	NO. 60	Location:			California	Project ;		MAO1.C	101	
0 11 01 0 0 0 0	Date Dri		<u>10-4-05</u>		Logged By:		<u>I Mart</u>		<u>Reviewed</u>	-			
					g Co., Inc.	Driller:		mador	<u>Method:</u>			em Aug	er
Bore Hole Diam		8			: 23 Ft	•			N/A	<u>Ft. St</u>		N/A	F
Casing Type:	PVC		<u> Diameter:</u>	2	In. Scher		40	<u>Interval:</u>		^	To:	3	Ft
Screen Type:	PVC		Diameter:	2	<u>In.</u> Slot	Size:	0.020	<u>In. Interval:</u>		<u>Ft.</u>	To:	23	F
Filter Pack Type		3 Sand				- w-		<u>Interval:</u>			To:	23	F
	ntonite							<u>Interval:</u>			To:	2	F
Grout Type: Typ			Sample ID	Lithologic				Interval:	0.5	Ft.	To:	<u>1.5</u>	F
Well Detail	Depth (Ft.)	PID (PPM)	Sample ID Blowcount	Lithologic Log				Description					
	- 2	0.0 -	7	CL	Clay With San Clay With San Damp. No Od Slightly Plastic Company	or	ve Gray	With Grayish Gre	en, Largely F	Plastic, A	d oderately	Stiff,	
	- 10	0.0	6 16		- Largely Plastic 	: Moderatel	y Stiff						
	- 16 18	-	17 50 For 6	sw	Sand With Cla Angular To Ro Dense, Wet, No -	und, Very i	el, Olive Tine Grav	Gray, Well Grade rel, Subangular Te	d, Very Fine o Subrounded	To Very d. Loose	Coarse : To Mode	Sand, erately	
	- 20 - 22		5 9 20 -	CL	-			Mostly Plastic, S					
	24 26 28	1	10		Clay With Sand No Odor .	a Pale Uliv	e, Large	ly To Mostly Plas	uc, sort To	Moderate	ely Stiff,	MOIST,	
		+	-	-				LEGEND					
	-30		\exists	r	-	Explanation:	-		<u>Contac</u>	ts:			
	- 1	7	7	ľ	□ Lo	cation Of R	ecovered	Drill Sample		. Solid Where (Certain		
i i	_32_				_ ■ ½	cation Of S emical Analy	ample Se	aled For		Dotted Approxi			
	_ ,	7					, 313						
	34 				– NR No	Recovery				Dashed Uncerta	in unere		
	- 1		7	F	☐ Gr	out				Hachure Gradatio	ed Where		
	— 36 —		7	F	– Be	ntonite							
		1		r	So	nd							
	- 38 - 		\exists										
ļ	- 40	1	1	F	Sc ل∐	reen			F	age 1 (Of 1		


Date Drilled: 10-4-05 Logged By: Cheryl Martin Reviewed By: Drilling Company: Woodward Drilling Co., Inc. Driller: Amador Method: Hollow Stem Auger		Project	R " Servic	totten Robl	bie	Location:	55 Santa	Todd	Road California	BORING Project	•	NO:	MW-6	
Cost Received Portilling Company, Woodward Drilling Co., Inc. Driller: Amador Method: Hollow Stem Auger Bare Hole Dammeter: 8 In. Depth Drillist; 23 Ft. Depth To Water Initiol: N/A Ft. Statis: N/A Ft. Costina Type: PVC Diameter: 2 In. Schollus: 40 Interval: 0.25 Ft. To: 3 Ft. Screen Type: PVC Diameter: 2 In. Schollus: 40 Interval: 3 Ft. To: 2.3 Ft. Tiller Pock Type: WS Sand Interval: 2 Ft. To: 2.3 Ft. Scal Type: Bentonite Interval: 1.5 Ft. To: 2.5 Ft. Scal Type: Bentonite Interval: 0.5 Ft. To: 1.5 Ft. Crout Type: Type I-II Coment Clay With Sand, Moderate Yellowish Brown/Grayte Green Slightly Picetic. Moderately Stiff, Damp, No Dater Clay With Sand, Moderate Yellowish Brown/Grayte Green Slightly Picetic. Moderately Stiff, Damp, No Dater Clay With Sand, Moderate Yellowish Brown Stiff Clay With Sand, Moderate Yellowish Brown Web Grazed, Vary Fine To Vary Coorse Sand, Angular To Round, Very Fine Green's Submignious To Stiff and Angular To Stiff Sand, Angular To Round, Very Fine Green's Submignious To Stiff and Angular To Stiff and Angu	EMMROTECH, INC.				140. 60							MAO 1.0	01	
Bors Hole Didmeter: 8 In	C-14 Bin- C- 05670				end Daillina							II CL	A	
Casing Type: PVC Diameter: 2 In. Schedule: 40 Interval: 0.25 Ft. To: 3 Ft. Screen Type: PVC Diameter: 2 In. Sid. Size: 0.020 Interval: 2 Ft. To: 23 Ft. To: 24 Ft. To: 25 Ft.					_									
Screen Tube:	· · · · · · · · · · · · · · · · · · ·			-			•			•			•	
Filter Pack Type: #3 Sand Interval: 2 Ft. To: 2.5 Ft. Sed. Type: Interval: 1.5 Ft. To: 2 Ft. To: 1.5 Ft. To: 1														
Saci Type: Type Type Cement				zia) (ictor.		<u> </u>	<u> </u>	.0.020						
County C														
Description			Cement											Ft.
CL Clay With Sand, Moderate Yellowish Brown/Grayish Green Slightly Plastic, Moderately Stiff, Demp., No Odor CL Moderate Yellowish Brown. Stiff Sandy Clay Dark Yellowish Brown. Stiff Sandy Clay Dark Yellowish Brown. Well Graded, Very Fine To Very Course Sand, Argular to Round, Very Fine To Very Course Sand, Argular to Round, Very Fine Gravel Subangular to Siderounded, Loose, With No Odor Sandy Clay Dark Greenish Gray, Mostly Plastic Soft, Demp To Moist LEGEND Legend Legend Legend No Recovered Drill Sample Sand Argular to Recovered Drill Sample Legend Sand Argular to Round, Very Fine Gravel Subangular to Siderounded, Loose, With No Odor CLay Clay Dark Greenish Gray, Mostly Plastic Soft, Demp To Moist Legend Legend No Recovered Drill Sample Sand Minera Repositation Control of Recovered Drill Sample Sand Minera Repositation Control of Court — Control of Court — Court — Control of Court —	Well Detail	Depth (Ft.)	PID (PPM)	Sample ID Blowcount	Lithologic Log									
Screen Page 1 Of 1		- 2	00 -	4 50 For 6 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	CL	Stiff, Damp, Moderate Yell Sandy Clay I Sandy Clay, I Sandy Clay, I No Odor No No Odor Sandy Clay, I Sa	owish Brown Dark Yellow Explanation Coation Of the ocation oc	vn. Stiff vish Gray, vish Gray, ish Gray, Recovered Sample Sealysis	Largely Plastic Marish Brown, Well Ce Gravel Subang	Graded, Very ular To Subi	Fine To S Fine To Counded, Moist Solid Where Approxi Dashed Uncerto Hachurg	Certain Where mote Where jin	J/Se	

	Project:	R	otten Robi e Station	bie	Location:	55 Santa	5 Todd Ro Rosa, Co	oad difornia	BORING Project	·	NO:	MW-7	
ENVIROTECH, INC.	Date Dr		10-4-05	NO. BU			-	iniornia			WAU I.U	101	
Cold Diver Ca 05670				rd Drilling	Logged By Co., Inc.		ryl Martin	-dor	Reviewed Method:		Ilaw Ct.	em Aug	
Bore Hole Diam		8		th Drilled:			n To Wate	idor r: Initial:	N/A	Ft. St		N/A	Ft
Casing Type:	PVC		Diameter:	2	In. Sche		40	Interval:	•		To:	3	Ft
Screen Type:	PVC)iameter:	2	In. Slot			n. Interval:		Ft.		23	Ft
Filter Pack Type		#3 Sand		_		<u> </u>		Interval:		Ft.	To:	23	Ft
Seal Type: Ber	ntonite							Interval:		Ft.	То:	2	Ft
Grout Type: Typ								Interval:	0.5	Ft.	To:	1.5	Ft
Well Detail	Depth (Ft.)	PID (PPM)	Sample ID Blowcount	Lithologic Log				Description					
				<u> </u>	_								
		-	_		- Clay With Sili Moderately S	t, Dark Ye tiff Damp	llowish Brown, No Odor	/Grayish Black	: Largely To	Mostly I	Plastic, S	oft To	
	- 4 -	0.0	- +□	-	— - Clay With Sa	nd, Đusky	Yellow Green,	, Mostly Plastic	c. Soft, Dam	ip, No O	dor		
	6 —	-	7 ∐ —		-								
	 8	-	_	CL	-								
	10	0.0	4 4 8		Sandy Clay, I	_ight Olive	Gray. Slightly	/ To Largely P	Plastic, Very	Soft, Da	mp, No C)dor	
	12-	_	۰۵ _		-								
	14	-	-		_								
	16	-	8 7 9		Clay With Sar Stiff, Moist, N	nd, Moderd No Odor	ate Olive Brow	rn/Light Olive	Brown, Large	ely Plasti	ic, Modero	otely	
	- 18	_			-								
	20		50 🗆 –		— Sand With Gr	avel, Olive	Gray, Well G	raded, Very Fil	ne To Very	Coarse S	iand, Angi	ular To	
	- 22	-	For –	sw	_ Kound, Very I	ine Grave	I, Subangular	To Subrounde	ed, Loose, We	et, No O	dor		
	 - 24		50 🔲 – For 5	<u> </u>	-								
		-	_		-								
		4	4	\ \									
	— 28 —	4	-	-	_		ı	EGEND					
		+	-	-			Ļ	EGEND					
	−30 −	\dashv	\dashv	F	-	Explanation	on:		Contac	cts:			
	+	+	-	 		ocation Of	Recovered Dr	ill Sample		_ Solid Where	Certain		
	32		_	-	_ ■ [ocation Of hemical Ar	Sample Seale alysis	d For		Dotted	Where		
	34					o Recovery				Approxi _ Dashed _	Where		
		4	-	-	1 7 - 71	rout				Uncerto	iin ed Where		
	— 36 —	-		-		entonite				Gradatio	ougl		
		-	4	<u> </u>	[5336]								
	— 38 —	7		-		and							
	40	1	1	r	<u> </u>	creen			1	Page 1 (Of 1		

	D- · ·		otten Robi		55 Todd Road BORING NO: GP-1B
APEX EMROTECH, INC.	D D			No. 60	Location: Santa Rosa, California Project # RMA01.001
1244 Pyrites Way ld River, Ca 95670	Date Dr		10-6-05		Logged By: Cheryl Martin Reviewed By:
	jurilling				g Co., Inc. Driller: Anthony Method: Direct Push
<u>re Hole Diam</u> sing Type:	<u>leter:</u> N/A	<u>3</u>	<u>In. Dep</u> Diameter:	th Drilled: N/A	
reen Type:	N/A		Diameter:	N/A N/A	In. Schedule: N/A Interval: N/A Ft. To: N/A In. Slot Size: N/A In. Interval: N/A Ft. To: N/A
er Pack Type		N/A	ZIGITIÇÇÇI.	IV/A	Interval: N/A Ft. To: N/A
	N/A				Interval: N/A Ft. To: N/A
out Type:	I-II Cem	nent			Interval: 0 Ft. To: 28.5
Well Detail	Depth (Ft.)	PID (PPM)	Sample ID Blowcount	Lithologic Log	Description
	- 2			CL GC	Clay Grayish Olive Green, Mostly Plastic Soft, Damp, No Odor Sandy Clay, Moderate Yellowish Brown, Nonplastic To Slightly Plastic, Moderately Stiff, Dry, No Odor Clay With Sand, Moderate Yellowish Brown/Dusky Yellow Green, Mostly Plastic, Moderately Stiff, Damp, No Odor Soft Sondy Clay, Dusky Yellow Green, Mostly Plastic, Soft To Moderately Stiff, Moist, No Odor Clay With Sand, Moderate Yellowish Brown/Dusky Yellow Green Mostly Plastic, Moderately Stiff, Damp, No Odor Clayey Gravel With Sand, Moderate Yellowish Brown, Well Graded, Very Fine To Caarse Sand, Angular To Round, Very Fine To Medium Gravel, Angular To Subrounded, Moderately Dense, Moist, No Odor Gravelly Sand With Clay, Moderate Yellowish Brown, Well Graded, Very Fine To Very Coarse, Angular To Round, Moderately Dense, Moist To Wet, No Odor Sandy Clay, Moderate Yellowish Brown, Mostly Plastic, Moderately Stiff, Moist, No Odor Clay With Sand Light Olive Gray, Largely Plastic, Moderately Stiff To Stiff, Damp, No Odor
	32 	-	- - -		LEGEND
	— 36 —				Explanation: Contacts:
	_			L	Location Of Recovered Drill Sample Solid Where Certain
	38				
				Ĺ	
		-	- - -	- - -	Location of Recovered Drill Sample Sample Where Certain Location of Sample Sealed For Dashed Where Uncertain Grout

	Project		otten Robi		55 Todd Road Location: Santa Rosa, California Project # RMA01.001
EMROTECH, NC.	Date Dr		10-6-05	NO. 60	
1244 Pyrites Way ld River, Ca 95670	\			and Drillin	Logged By: Cheryl Martin Reviewed By: g Co., Inc Driller: Anthony Method: Direct Push
ore Hole Diam		<u> </u>			
sing Type:	N/A		<u>in. bep</u> Diameter:	th Drilled N/A	
reen Type:	N/A		Diameter:	N/A	
ter Pack Type		<u>_</u> N/A	numeter.		•
-	N/A	1,77,			Interval: N/A Ft. To: N/A Interval: N/A Ft. To: N/A
	I—II Cen	nent			Interval: N/A Ft. To: N/A Interval: 0 Ft. To: 29
Well Detail	Depth (Ft.)	PID (PPM)	Sample ID	Lithologic Log	Description Pt. 10. 29
	1 (12)	(FFM)	Blowcount	Log	Clay, Light Olive Gray, Mostly Plastic, Soft, Damp, No Odor
	+ +	4			-
	├ 2 -	\dashv		}	_
	├	-	-	ŀ	-
	- 4 -		H-i		— Changes To Olive Gray in Color
	F 4	4		-	- Changes To Grayish Olive Green In Color
	├ 6 ├	\dashv		}	Sandy Clay, Moderate Yellowish Brown, Nonplastic To Slightly Plastic, Moderately Dense, Dry To Damp, No Odor
	 -	4		CL	Dense, Dry to Damp, No Odor Clay, Moderate Yellowish Brown, Slightly Plastic, Stiff, Damp, No Odor
	⊢ 8 −		H-H	}	
	F =	4			Clay With Sand, Dusky Yellow Green, Mostly Plastic, Soft, Damp
	10-			-	_
	 	4		[- Sandy Clay, Moderate Yellowish Brown/Grayish Green, Largely Plastic, Soft To
	12-	4	H = H	<u> </u>	Moderately Stiff, Damp, No Odor
	<u> </u>	4	4		Clayey Sand, Grayish Green, Poorly Graded, Medium Sand, Moderately Dense, Moist
	14-	_		sc	To Wet, No Odor
	- -	4		CL	Sandy Clay, Moderate Yellowish Brown/Grayish Green, Slightly Plastic To Largely Plastic, Stiff, Damp To Moist
	16	4	H = H		Gravelly Sand With Clay, Moderate Yellowish Brown With Gravish Green, Well Graded.
		4			Very Fine To Very Coarse, Angular To Subrounded, Very Fine To Medium Gravel, Subangular To Subrounded, Loose To Moderately Dense, Moist To Wet
	18	4		ļ	_
		4			
	20-	4	$H \rightarrow$	sw _	_
	<u> </u>	4			
	22				_
	├	4			
	24	4	$H \rightarrow$	 	_
		4		CL	Sandy Clay, Moderate Yellowish Brown, Largely Plastic, Soft To Moderately Stiff, Wet, No Odor
	<u> </u>	4		sw -	Gravelly Sand With Clay, Moderate Yellowish Brown, Well Graded, Very Fine To Very — Coarse Sand, Angular To Subrounded, Very Fine To Medium Gravel, Angular To Subrounded, Loose To Moderately Dense, Wet, No Odor
	F 4	4			•
	28	\dashv	$H \rightarrow$		Sandy Clay, Dusky Yellow Green, Largely Plastic To Mostly Plastic, Soft To Moderately Stiff, Damp To Moist, No Odor
	├	4		CL	
	- 30 -	\dashv	⊣'	\	_
	<u> </u> -	4	4	\	
	32	4	_	/ [_
	-	4	4	1	
	34	\dashv		<u> </u>	
	├	_		<u> </u>	LEGEND
	— 36 —		_		Explanation: Contacts:
	<u> </u>			L	Location Of Recovered Drill Sample Solid Where Certain
	38				Location Of Sample Sealed For Dashed Where
		_}	_]		<u> </u>
	L 40_L	1			Grout

		Project	R : Service	Rotten Rob e Station	bie No 60	55 Todd Road Location: Santa Rosa, California Project # RMA01.001
EMIROTE	CH, INC.	Date D		10-6-05	110. 00	
11244 Pyr Gold River,	rites Way Ca 95670				ard Drillin	Logged By: Cheryl Martin Reviewed By: g Co., Inc. Driller: Anthony Method: Direct Push
Bore Ho	le Diam		3		th Drilled	
Casing 1		N/A		Diameter:	N/A	In. Schedule: N/A Interval: N/A Ft. To: N/A F
Screen	Туре:	N/A		Diameter:	N/A	In. Slot Size: N/A In. Interval: N/A Ft. To: N/A F
ilter Po	ick Type	:	N/A			Interval: N/A Ft. To: N/A F
Seal Typ	e:	N/A				Interval: N/A Ft. To: N/A F
Frout Ty		l-II Cer				Interval: 0 Ft. To: 24 F
	Well Detail	Depth (Ft.)	PID (PPM)	Sample ID Blowcount	Lithologic Log	Description
		- 10	8.5 - 115 - 00	Blowcount	CL	Clay Olive Gray, Largely Plastic Moderately Stiff, Damp, Slight Odor Mostly Plastic, Moderate Odor Clay With Sand, Moderate Yellowish Brown/Graylsh Green. Slightly Plastic. Moderately Stiff To Stiff, Damp, Slight Odor Grayish Olive Green, Mostly Plastic. Soft Damp To Moist, Slight Odor Moderate Yellowish Brown With Grayish Green, Largely Plastic. Moderately Stiff Damp To Moist, No Odor Grayish Olive Green. Mostly Plastic, Soft Gravelly Sand With Clay, Moderate Yellowish Brown, Well Graded, Very Fine To Very Coarse Sand, Angular To Round, Very Fine To Medium Gravel, Angular To Subrounded, Moderately Dense, Moist To Wet, No Odor Clay With Sand, Grayish Green. Mostly Plastic, Soft To Moderately Stiff. Damp. No Odor LEGEND Explanation: Contacts: Location of Recovered Drill Sample Solid
	Ĺ]		_[Location Of Recovered Drill Sample Solid
		_ 38				where Certain Location Of Sample Sealed For Dashed Where
		. ~]				
		40	7	7	Γ	Grout



California Laboratory Services

3249 Fitzgerald Road Rancho Cordova, CA 95742

October 17, 2005

CLS Work Order #: COJ0304 COC #: 56248

Rebekah Westrup APEX Envirotech Inc. - Gold River 11244 Pyrites Way Gold River, CA 95670

Project Name: Rotten Robbie Service Station

Enclosed are the results of analyses for samples received by the laboratory on 10/07/05 16:50. Samples were analyzed pursuant to client request utilizing EPA or other ELAP approved methodologies. I certify that the results are in compliance both technically and for completeness

Analytical results are attached to this letter. Please call if we can provide additional assistance

Sincerely,

James Liang, Ph.D. Laboratory Director

CA DOHS ELAP Accreditation/Registration number 1233

10/17/05 11:22

APEX Envirotech Inc - Gold River

11244 Pyrites Way Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

Project Number: RMA01 001 Project Manager: Rebekah Westrup

COC #: 56248

Extractable Petroleum Hydrocarbons by EPA Method 8015M

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
GP-5B-27.5' (COJ0304-01) Soil	Sampled: 10/06/05 12:2	8 Receive	ed: 10/07	/05 16:50		······································		······································	
Diesel	ND	1 0	mg/kg	1	CO07666	10/10/05	10/10/05	EPA 8015M	
GP-1B-25' (COJ0304-02) Soil	Sampled: 10/06/05 14:45	Received	: 10/07/0	5 16:50					
Diesel	ND	1.0	mg/kg	1	CO07666	10/10/05	10/10/05	EPA 8015M	
GP-11-5' (COJ0304-03) Soil S	Sampled: 10/06/05 16:21	Received:	10/07/05	16:50					
Diesel	ND	1 0	mg/kg	1	CO07666	10/10/05	10/10/05	EPA 8015M	
GP-11-10' (COJ0304-04) Soil	Sampled: 10/06/05 16:27	Received:	10/07/05	5 16:50					
Diesel	ND	1 0	mg/kg	1	CO07666	10/10/05	10/10/05	EPA 8015M	
GP-11-15' (COJ0304-05) Soil	Sampled: 10/06/05 16:32	Received:	10/07/05	5 16:50					
Diesel	ND	10	mg/kg	1	CO07666	10/10/05	10/10/05	EPA 8015M	
GP-11-21.5' (COJ0304-06) Soil	Sampled: 10/06/05 16:50	0 Receive	d: 10/07/	05 16:50					
Diesel	ND	10	mg/kg	1	CO07666	10/10/05	10/10/05	EPA 8015M	
SP-1 (A-D) Composite (COJ030	4-11) Soil Sampled: 10/	06/05 17:10	Receiv	ed: 10/07/	05 16:50				
Diesel	ND	1 0	mg/kg	1	CO07666	10/10/05	10/10/05	EPA 8015M	

10/17/05 11:22

APEX Envirotech Inc - Gold River

11244 Pyrites Way Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

Project Number: RMA01 001

Project Manager: Rebekah Westrup

COC #: 56248

Gas/BTEX by GC PID/FID

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
GP-5B-27.5' (COJ0304-01) Soil	Sampled: 10/06/05 12:2	8 Receiv	ed: 10/07	/05 16:50					
Gasoline	ND	1000	μg/kg	1	CO07714	10/11/05	10/11/05	8015M/8021B	•
Benzene	ND	5.0	H	n	н	11	И	H	
Ioluene	ND	5 0	a a	н	U	U	a	IJ	
Ethylbenzene	5.4	5 0	U	n	н	п	U	D	
Xylenes (total)	ND	10))			н	0	H	
Surrogate. o-Chlorotoluene (Gas)		105 %	65-	135	ч	н	#	H	
GP-1B-25' (COJ0304-02) Soil S	Sampled: 10/06/05 14:45	Received	: 10/07/0	5 16:50					
Gasoline	ND	1000	μg/kg	1	CO07714	10/11/05	10/11/05	8015M/8021B	
Benzene	ND	5 0	11	1	U	0	н	н	
Toluene	ND	5 0	D	11	11	D	a a	n	
Ethylbenzene	ND	5.0	н	11	H	H	ŋ	11	
Xylenes (total)	ND	10	11	11	11	п	н	"	
Surrogate o-Chlorotoluene (Gas)		101 %	65-	135	H	н	n .	,,	
GP-11-5' (COJ0304-03) Soil Sa	mpled: 10/06/05 16:21 F	Received:	10/07/05	16:50					
Gasoline	ND	1000	μg/kg	1	CO07714	10/11/05	10/11/05	8015M/8021B	
Benzene	ND	5 0	"	11	U	41	11	н	
Toluene	ND	5.0	Ω	u	II .	ij	U	ti	
Ethylbenzene	ND	5 0	Ħ	U	H	11	U	U	
Xylenes (total)	ND	10	u	н	п	И	11	0	
Surrogate. o-Chlorotoluene (Gas)		105 %	65-	1.35	n	"	n	"	
GP-11-10' (COJ0304-04) Soil S	ampled: 10/06/05 16:27	Received:	10/07/05	16:50					
Gasoline	ND	1000	μg/kg	1	CO07714	10/11/05	10/11/05	8015M/8021B	
Benzene	ND	5 0	II.	U	D	n	11	· ·	
I oluene	5.9	5 0	п	11	11	и	U	ш	
Ethylbenzene	ND	5 0	U	н	н)	11	U	
Xylenes (total)	ND	10	D	11	ı	ti .	н	H	
Surrogate. o-Chlorotoluene (Gas)		107 %	65-135		"	н	u	6	

10/17/05 11:22

APEX Envirotech Inc. - Gold River

11244 Pyrites Way Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

Project Number: RMA01 001

Project Manager: Rebekah Westrup

COC #: 56248

Gas/BTEX by GC PID/FID

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
GP-11-15' (COJ0304-05) Soil	Sampled: 10/06/05 16:32	Received	10/07/05	16:50				## T T T T T T T T T T T T T T T T T T	•
Gasoline	ND	1000	μg/kg	1	CO07714	10/11/05	10/11/05	8015M/8021B	***************************************
Benzene	ND	5 0	ti .	II.	Ħ	U	U	p	
Ioluene	ND	5 0	U	1)	II.	Ħ	17	н	
Ethylbenzene	ND	5.0	H	1	II.	н	н	я	
Xylenes (total)	ND	10	11		н	11	u		
urrogate o-Chlorotoluene (Gas)		996%	65-1	3.5	<i>H</i>	н	"	u	
GP-11-21.5' (COJ0304-06) Soil	Sampled: 10/06/05 16:50) Receive	d: 10/07/0	5 16:50					
Gasoline	ND	1000	μg/kg	1	CO07714	10/11/05	10/11/05	8015M/8021B	
Benzene	ND	5 0	H	17		IT	II.	H	
Toluene	ND	5.0	tt	a a	11	п	Ħ	tt	
Ethylbenzene	ND	5 0	II .	0	я	n .	U	U	
Xylenes (total)	ND	10	D)7	u	n	II .	II .	
urogate. o-Chlorotoluene (Gas)		103 %	65-1	35	н	v	#	u	
SP-1 (A-D) Composite (COJ030	4-11) Soil Sampled: 10/0	06/05 17:10	Receive	ed: 10/07/	05 16:50				
Gasoline	ND	1000	μg/kg	1	CO07714	10/11/05	10/11/05	8015M/8021B	
Benzene	ND	5 0	II .	0	м	a a	11	п	
Toluene	ND	5 0	"	D	16	U	U	ıı.	
Ethylbenzene	ND	5.0	M	н	U	D	D		
Xylenes (total)	ND	10	ii .	11	D	H	11	II.	
Surrogate o-Chlorotoluene (Gas)		102 %	65-1	35	μ	"	"	v	

10/17/05 11:22

APEX Envirotech Inc. - Gold River

11244 Pyrites Way Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

Project Number: RMA01 001 Project Manager: Rebekah Westrup

COC #: 56248

Metals by EPA 6000/7000 Series Methods

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes	
SP-1 (A-D) Composite (COJ0304-11) Soil Sampled: 10/06/05 17:10 Received: 10/07/05 16:50										
Lead	4.3	2.5	mg/kg	1	CO07713	10/11/05	10/11/05	EPA 6010B		

10/17/05 11:22

APEX Envirotech Inc - Gold River

11244 Pyrites Way Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

Project Number: RMA01 001 Project Manager: Rebekah Westrup

COC #: 56248

Non-halogenated Organic Compounds by EPA 8015

I .									
Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
GP-5B-27.5' (COJ0304-01) So	il Sampled: 10/06/05 12:	28 Receiv	ed: 10/07	/05 16:50			****	****	
Ethanol	ND	5 0	mg/kg	1	CO07775	10/13/05	10/13/05	EPA 8015B	
Methanol	ND	5.0	11	11	н	11	+	a a	
GP-1B-25' (COJ0304-02) Soil	Sampled: 10/06/05 14:45	Received	1: 10/07/0	5 16:50					
Ethanol	ND	5.0	mg/kg	1	CO07775	10/13/05	10/13/05	EPA 8015B	
Methanol	ND	5.0	14	n	н	u	*1	1	
GP-11-5' (COJ0304-03) Soil	Sampled: 10/06/05 16:21	Received:	10/07/05	16:50					
Ethanol	ND	5.0	mg/kg	1	CO07775	10/13/05	10/13/05	EPA 8015B	
Methanol	ND	5 0	R	н	N	11	*1	11	
GP-11-10 ¹ (COJ0304-04) Soil	Sampled: 10/06/05 16:27	Received	: 10/07/0	5 16:50					
Ethanol	ND	5 0	mg/kg	1	CO07775	10/13/05	10/13/05	EPA 8015B	
Methanol	ND	5 0	#1	a	11	u	Ħ	Ħ	
GP-11-15' (COJ0304-05) Soil	Sampled: 10/06/05 16:32	Received	: 10/07/05	5 16:50					
Ethanol	ND	5 0	mg/kg	1	CO07775	10/13/05	10/13/05	EPA 8015B	
Methanol	ND	5 0	u	u	11	п	O	u	
GP-11-21.5' (COJ0304-06) Soil	Sampled: 10/06/05 16:5	0 Receive	d: 10/07/	05 16:50					
Ethanol	ND	5 0	mg/kg	1	CO07775	10/13/05	10/13/05	EPA 8015B	
Methanol	ND	5.0	U	II.	II .	11	II .	n .	
SP-1 (A-D) Composite (COJ03	04-11) Soil Sampled: 10/	06/05 17:10	0 Receiv	ed: 10/07/	05 16:50				
Ethanol	ND	5 0	mg/kg	1	CO07775	10/13/05	10/13/05	EPA 8015B	
Methanol	ND	5.0	D	"	D	11	II	n .	

10/17/05 11:22

APEX Envirotech Inc - Gold River

11244 Pyrites Way

Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: CO J0304

Project Number: RMA01 001

COC #: 56248

Project Manager: Rebekah Westrup

Analyte	F Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
GP-5B-27.5' (COJ0304-01) So	il Sampled: 10/06/05 12:28					P		4 - 8-35 - 92 - 53 - 53	
Di-isopropyl ether	ND	5 0	μg/kg	1	CO07710	10/11/05	10/11/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5.0	u T	ii .	11	н	I+	11	
Methyl tert-butyl ether	ND	5 0	11	H	1)	11	a	U	
tert-Amyl methyl ether	ND	5 0	"	н	IT	D.	n	II.	
Tert-butyl alcohol	ND	50	*1		*1	H		н	
1,2-Dibromoethane (EDB)	ND	5.0	u u	U	0	n	H	11	
1,2-Dichloroethane	ND	5.0	11		U		0		
Surrogate Toluene-d8		978%	60-	140	,,	"	"	"	
GP-1B-25' (COJ0304-02) Soil	Sampled: 10/06/05 14:45	Received	: 10/07/0	5 16:50					
Di-isopropyl ether	ND	5.0	μg/kg	1	CO07710	10/11/05	10/11/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5 0	11	II.	11	IF	n .	14	
Methyl tert-butyl ether	ND	5 0	"	14	0	Ħ	H	ti .	
tert-Amyl methyl ether	ND	5 0	11	**	11	u		u	
Tert-butyl alcohol	ND	50	u	n	н	D	1	n	
1,2-Dibromoethane (EDB)	ND	5 0	U	D	п	н	11	И	
1,2-Dichloroethane	ND	5.0	H	н	0	11	н	n .	
Surrogate Toluene-d8		102 %	60-	140	,,	"	v	"	
GP-11-5' (COJ0304-03) Soil	Sampled: 10/06/05 16:21 R	eceived:	10/07/05	16:50					
Di-isopropyl ether	ND	5.0	μg/kg	1	CO07710	10/11/05	10/11/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5 0	U	D	,	D	n	U	
Methyl tert-butyl ether	37	5 0	D	*	"	a	"	11	
tert-Amyl methyl ether	ND	5 0	н	н	D	11	PT	н	
Tert-butyl alcohol	28000	2500	9	50	Ħ	n.	10/13/05	41	
l,2-Dibromoethane (EDB)	ND	5 0	II.	1	н	D	10/11/05	u	
1,2-Dichloroethane	ND	5.0	H	и	а	H .		D	
Surrogate: Toluene-d8		998%	60-1	140	н	n	"	n	

10/17/05 11:22

APEX Envirotech Inc - Gold River

11244 Pyrites Way Gold River, CA 95670

Project Manager: Rebekah Westrup

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

Project Number: RMA01 001

COC #: 56248

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
GP-11-10' (COJ0304-04) Soil	Sampled: 10/06/05 16:27	Received	: 10/07/05	16:50					
Di-isopropyl ether	ND	5.0	μg/kg	1	CO07710	10/11/05	10/11/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5 0	II	ü	н	н	Ø	U	
Methyl tert-butyl ether	19	5.0	17	U	n	U	U	D	
tert-Amyl methyl ether	ND	5.0	ห	11	"	D.	10	н	
I ert-butyl alcohol	25000	2500	n	50	11	†I	10/13/05	Ħ	
1,2-Dibromoethane (EDB)	ND	5 0	D	1	1	11	10/11/05	n	
1,2-Dichloroethane	ND	5.0	н	N .	J	u	n	t)	
Surrogate. Toluene-d8		103 %	60	140	"	,	"	n	
GP-11-15' (COJ0304-05) Soil	Sampled: 10/06/05 16:32	Received	: 10/07/05	16:50					
Di-isopropyl ether	ND	5 0	μg/kg	1	CO07754	10/12/05	10/12/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5 0	D	u	11	If	М	н	
Methyl tert-butyl ether	ND	5.0	Ħ	"	a a	н	u	u	
tert-Amyl methyl ether	ND	5.0	11	H	U	a a	n	11	
I er t-butyl alcohol	540	50	n	11	Ħ	H	10	11	
1,2-Dibromoethane (EDB)	ND	5 0	n	U	И	i)	Ħ	re .	
1,2-Dichloroethane	ND	5.0	#	n	11	N	11	(1	
Surrogate. Toluene-d8		101 %	60-1	140	"	"	n	"	
GP-11-21.5' (COJ0304-06) Soil	Sampled: 10/06/05 16:50	Receive	d: 10/07/0	5 16:50					
Di-isopropyl ether	ND	5.0	μg/kg	1	CO07710	10/11/05	10/11/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5 0	u	**	U	u	U	II .	
Methyl tert-butyl ether	200	5.0	U	9	**	"	,,	0	
tert-Amyl methyl ether	ND	5.0	н	U	11	H	*1	n	
I ert-butyl alcohol	54	50	u	17	n	U	II	11	
1,2-Dibromoethane (EDB)	ND	5 0	U	н	IJ	n	n .	u .	
1,2-Dichloroethane	ND	5.0	и	a	"		H	0	 .
Surrogate. Toluene-d8		101 %	60-1	40	o	u	n	"	

10/17/05 11:22

APEX Envirotech Inc - Gold River

11244 Pyrites Way Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

Project Number: RMA01 001

COC #: 56248

Project Manager: Rebekah Westrup

Volatile Organic Compounds by EPA Method 8260B

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
SP-1 (A-D) Composite (COJ0304-11) Soil	Sampled: 1	0/06/05 17:10	Receiv	ved: 10/07/	05 16:50	-			
Di-isopropyl ether	ND	5 0	μg/kg	1	CO07664	10/10/05	10/10/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5 0		н	II.	**	u	11	
Methyl tert-butyl ether	5.1	5 0	11	11	11	U	1	1	
tert-Amyl methyl ether	ND	5 0	D	1	9	II.	u.	11	
Tert-butyl alcohol	1700	50	н	11	H	11	m	11	
1,2-Dibromoethane (EDB)	ND	5.0	н	н	17	11	11	11	
1,2-Dichloroethane	ND	5.0	U	11	н	1		a	
Surrogate Toluene-d8		101 %	60-	140	n	"	н	"	

CA DOHS ELAP Accreditation/Registration Number 1233

10/17/05 11:22

APEX Envirotech Inc - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

11244 Pyrites Way Gold River, CA 95670

Project Number: RMA01 001

COC #: 56248

Project Manager: Rebekah Westrup

Extractable Petroleum Hydrocarbons by EPA Method 8015M - Quality Control

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch CO07666 - LUFI-DHS GCNV										
Blank (CO07666-BLK1)				Prepared	& Analyzo	ed: 10/10/	05			
Diesel	ND	10	mg/kg							
Motor Oil	ND	1.0	1)							
LCS (CO07666-BS1)				Prepared	& Analyze	ed: 10/10/	05			
Diesel	40 2	10	mg/kg	50 0		80 4	65-135			
LCS Dup (CO07666-BSD1)				Prepared a	& Analyze	ed: 10/10/	05			
Diesel	41 2	10	mg/kg	50 0		82 4	65-135	2 46	30	
Matrix Spike (CO07666-MS1)	Sou	irce: COJ03:	31-01	Prepared 6	& Analyze	ed: 10/10/0	05			
Diesel	43 1	1 0	mg/kg	50.0	ND	86 2	59-138			
Matrix Spike Dup (CO07666-MSD1)	Sou	irce: COJ03.	31-01	Prepared a	& Analyze	ed: 10/10/0	05			
Diesel	40 8	10	mg/kg	50 0	ND	816	59-138	5 48	37	-

10/17/05 11:22

APEX Envirotech Inc. - Gold River

11244 Pyrites Way Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

Project Number: RMA01 001

Project Manager: Rebekah Westrup

COC #: 56248

Gas/BTEX by GC PID/FID - Quality Control

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch CO07714 - EPA 5030 Soil GC										
Blank (CO07714-BLK1)				Prepared	& Analyze	d: 10/11/	05			
Gasoline	ND	1000	μg/kg							
Benzene	ND	5 0	11							
Toluene	ND	5 0	U							
Ethylbenzene	ND	50	**							
Xylenes (total)	ND	10	н							
Surrogate o-Chlorotoluene (Gas)	103		"	100		10.3	65-135			
LCS (CO07714-BS1)				Prepared 6	& Analyze	:d: 10/11/0	05			
Gasoline	2540	1000	μg/kg	2500		102	65-135			
Surrogate o-Chlorotoluene (Gas)	10.3		н	100		103	65-135			
LCS Dup (CO07714-BSD1)				Prepared &	& Analyze	d: 10/11/0)5			
Gasoline	2760	1000	μg/kg	2500		110	65-135	8 30	30	
Surrogate o-Chlorotoluene (Gas)	106		n	100		106	65-135			•••

10/17/05 11:22

APEX Envirotech Inc - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

11244 Pyrites Way Gold River, CA 95670

Project Number: RMA01 001

COC #: 56248

Project Manager: Rebekah Westrup

Metals by EPA 6000/7000 Series Methods - Quality Control

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch CO07713 - EPA 3050B										•
Blank (CO07713-BLK1)				Prepared	& Analyze	ed: 10/11/	05			
Lead	ND	2 5	mg/kg							
LCS (CO07713-BS1)				Prepared	& Analyze	ed: 10/11/	05			
Lead	23 9	2 5	mg/kg	25 0		95 6	75-125			
LCS Dup (CO07713-BSD1)				Prepared of	& Analyze	ed: 10/11/	05			
Lead	24.1	2 5	mg/kg	25 0		96 4	75-125	0.833	25	
Matrix Spike (CO07713-MS1)	Soi	ırce: COJ03	51-01	Prepared of	& Analyze	ed: 10/11/0	05			
I.ead	27 8	2 5	mg/kg	25.0	7 4	81.6	75-125			
Matrix Spike Dup (CO07713-MSD1)	Soi	irce: COJ03	51-01	Prepared of	& Analyze	ed: 10/11/0)5			
Lead	27 8	2 5	mg/kg	25 0	7 4	816	75-125	0 00	30	

Fax: 916-638-4510

10/17/05 11:22

APEX Envirotech Inc - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

11244 Pyrites Way Gold River, CA 95670

Project Number: RMA01 001 Project Manager: Rebekah Westrup

COC #: 56248

Non-halogenated Organic Compounds by EPA 8015 - Quality Control

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch CO07775 - LUFI-DHS GCNV										
Blank (CO07775-BLK1)				Prepared	& Analyzo	ed: 10/13/	05			
Ethanol	ND	50	mg/kg	•					·	
Methanol	ND	5 0	h							
LCS (CO07775-BS1)				Prepared	& Analyze	ed: 10/13/0	05			
Methanol	52 5	5 0	mg/kg	50.0		105	75-125			
LCS Dup (CO07775-BSD1)				Prepared	& Analyze	ed: 10/13/0	05 .			
Methanol	50.3	5 0	mg/kg	50 0		101	75-125	4 28	30	
Matrix Spike (CO07775-MS1)	Soi	irce: COJ03	04-11	Prepared o	& Analyze	ed: 10/13/0)5			
Methanol	44 6	5 0	mg/kg	50 0	ND	89 2	75-125	•		
Matrix Spike Dup (CO07775-MSD1)	Sou	irce: COJ030	04-11	Prepared a	& Analyze	ed: 10/13/0)5			
Methanol	39 0	5 0	mg/kg	50.0	ND	78 0	75-125	13 4	30	

10/17/05 11:22

APEX Envirotech Inc - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

11244 Pyrites Way

Project Number: RMA01 001

Gold River, CA 95670

Project Manager: Rebekah Westrup

COC #: 56248

		Reporting		Spike	Source		%REC		RPD	
Analyte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Note
Batch CO07664 - EPA 5030 Soil MS										
Blank (CO07664-BLK1)				Prepared	& Analyze	ed: 10/10/	05			
Di-isopropyl ether	ND	5 0	μg/kg							
Ethyl tert-butyl ether	ND	5 0	IT							
Methyl tert-butyl ether	ND	5.0	11							
tert-Amyl methyl ether	ND	5 0	U							
Iert-butyl alcohol	ND	50	n							
Surrogate Toluene-d8	49.4	.,	n	50 0	•	988	60-140			
LCS (CO07664-BS1)				Prepared	& Analyze	ed: 10/10/	05			
Methyl tert-butyl ether	42 2	5 0	μg/kg	50.0		84.4	60-140			
Surrogate Toluene-d8	50 1		"	50 0		100	60-140			
LCS Dup (CO07664-BSD1)				Prepared a	& Analyze	d: 10/10/	05			
Methyl tert-butyl ether	36 8	5 0	μg/kg	50.0		73 6	60-140	13.7	30	
Surrogate Toluene-d8	50.7		n	50 0		101	60-140			
Matrix Spike (CO07664-MS1)	Sour	ce: COJ012	27-10	Prepared a	& Analyze	d: 10/10/0)5			
Methyl tert-butyl ether	45 1	5 0	μg/kg	50.0	ND	90 2	60-140			
Surrogate Toluene-d8	51.1		п	50 0		102	60-140			
Matrix Spike Dup (CO07664-MSD1)	Sour	ce: COJ012	27-10	Prepared &	& Analyze	d: 10/10/0)5			
Methyl tert-butyl ether	49 5	5 0	μg/kg	50.0	ND	99 0	60-140	9 30	30	
Surrogate Toluene-d8	51 2		"	50 0		102	60-140			
Batch CO07710 - EPA 5030 Soil MS										
Blank (CO07710-BLK1)				Prepared &	k Analyze	d: 10/11/0)5			
Di-isopropyl ether	ND	5 0	μg/kg							
Ethyl tert-butyl ether	ND	50	н							
Methyl tert-butyl ether	ND	5.0	11							
ert-Amyl methyl ether	ND	5 0	U							
ert-butyl alcohol	ND	50	ıı							
Surrogate Toluene-d8	50.5		"	50.0		101	60-140			

10/17/05 11:22

APEX Envirotech Inc - Gold River

11244 Pyrites Way Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

Project Number: RMA01 001 Project Manager: Rebekah Westrup

COC #: 56248

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch CO07710 - EPA 5030 Soil MS			21110	23701	-140410				2nt	1.505
LCS (CO07710-BS1)		н -		Prepared	& Analyze	-d- 10/11/	 ეร			
Methyl tert-butyl ether	44 7	5 0	μg/kg	50.0	Anatyzt	89 4	60-140			
Surrogate Toluene-d8	.52 2		"	50 0		104	60-140			
LCS Dup (CO07710-BSD1)				Prepared a	& Analyze	:d: 10/11/0	05			
Methyl tert-butyl ether	50 3	5 0	μg/kg	50 0		101	60-140	11.8	30	
Surrogate Toluene-d8	.50.9		"	50 0		102	60-140	• • • • • • • • • • • • • • • • • • • •		
Matrix Spike (CO07710-MS1)	Sou	rce: COJ02	78-03	Prepared a	& Analyze	:d: 10/11/0)5			
Methyl tert-butyl ether	47 2	5.0	μg/kg	50 0	ND	94.4	60-140			
Surrogate Toluene-d8	52 I		"	50 0		104	60-140			
Matrix Spike Dup (CO07710-MSD1)	Sou	rce: COJ02	78-03	Prepared a	& Analyze	d: 10/11/0)5			
Methyl tert-butyl ether	44 8	5 0	μg/kg	50 0	ND	89.6	60-140	5 22	30	
Surrogate Toluene-d8	49.3		H	50 0		98 6	60-140			
Batch CO07754 - EPA 5030 Soil MS										
Blank (CO07754-BLK1)				Prepared 2	& Analyze	d: 10/12/0)5		*************************************	
Di-isopropyl ether	ND	5 0	μg/kg							
Ethyl tert-butyl ether	ND	50	"							
Methyl tert-butyl ether	ND	5 0	"							
ert-Amyl methyl ether	ND	5 0	n							
ert-butyl alcohol	ND	50	n							
,2-Dibromoethane (EDB)	ND	5 0	м							
2-Dichloroethane	ND	50	11							
Benzene	ND	5.0	U							
Ethylbenzene	ND	50	u.							
oluene	ND	50	H							
(ylenes (total)	ND	10	11							
cylches (total)	1125									

10/17/05 11:22

APEX Envirotech Inc - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

11244 Pyrites Way Gold River, CA 95670

Project Number: RMA01 001 Project Manager: Rebekah Westrup

COC #: 56248

		Reporting		Spike	Source		%REC		RPD	
Analyte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch CO07754 - EPA 5030 Soil MS										
LCS (CO07754-BS1)				Prepared	& Analyz	ed: 10/12/	05			
Methyl tert-butyl ether	39 6	5 0	μg/kg	50 0		79 2	60-140			
Surrogate Toluene-d8	.52 7		н	50 0		10.5	60-140			
LCS Dup (CO07754-BSD1)				Prepared	& Analyz	ed: 10/12/	05			
Methyl tert-butyl ether	44 4	5 0	μg/kg	50 0		88 8	60-140	11.4	30	
Surrogate Toluene-d8	53 5		"	50 0		107	60-140			
Matrix Spike (CO07754-MS1)	Sou	arce: COJ03	39-11	Prepared	& Analyz	ed: 10/12/	05			
Methyl tert-butyl ether	42 6	5 0	μg/kg	50.0	ND	85 2	60-140			
Surrogate Toluene-d8	51.5		11	50 0		103	60-140			
Matrix Spike Dup (CO07754-MSD1)	Sou	irce: COJ03	39-11	Prepared	& Analyze	ed: 10/12/0	05			
Methyl tert-butyl ether	44.2	5 0	μg/kg	50.0	ND	88 4	60-140	3 69	30	
Surrogate Toluene-d8	50 2		n	50 0		100	60-140			

10/17/05 11:22

APEX Envirotech Inc - Gold River

11244 Pyrites Way Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: COJ0304

Project Number: RMA01 001

COC #: 56248

Project Manager: Rebekah Westrup

Notes and Definitions

DEI Analyte DETECTED

ND Analyte NOT DETECTED at or above the reporting limit

NR Not Reported

dry Sample results reported on a dry weight basis

RPD Relative Percent Difference

3249 Fitzgerald Road Rancho Cordova, CA 95742

October 12, 2005

CLS Work Order #: COJ0127 COC #: 56247

Rebekah Westrup APEX Envirotech Inc. - Gold River 11244 Pyrites Way Gold River, CA 95670

Project Name: Rotten Robbie Service Station

Enclosed are the results of analyses for samples received by the laboratory on 10/05/05 10:55 Samples were analyzed pursuant to client request utilizing EPA or other ELAP approved methodologies. I certify that the results are in compliance both technically and for completeness.

Analytical results are attached to this letter. Please call if we can provide additional assistance

Sincerely,

James Liang, Ph.D. Laboratory Director

CA DOHS ELAP Accreditation/Registration number 1233

10/12/05 15:39

APEX Envirotech Inc - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: CO J0127

11244 Pyrites Way Gold River, CA 95670

Project Number: RMA01 001 Project Manager: Rebekah Westrup

COC#: 56247

Extractable Petroleum Hydrocarbons by EPA Method 8015M

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
MW-5-6' (COJ0127-01) Soil	Sampled: 10/04/05 10:15	Received:	10/05/05	10:55					
Diesel	ND	1.0	mg/kg	1	CO07573	10/05/05	10/06/05	EPA 8015M	
MW-5-10.5' (COJ0127-02) Soil	Sampled: 10/04/05 10:1	8 Receive	ed: 10/05/	05 10:55					
Diesel	ND	10	mg/kg	1	CO07573	10/05/05	10/06/05	EPA 8015M	
MW-5-15' (COJ0127-03) Soil	Sampled: 10/04/05 10:23	Received	: 10/05/05	10:55					
Diesel	ND	10	mg/kg	1	CO07573	10/05/05	10/06/05	EPA 8015M	
MW-5-23' (COJ0127-04) Soil	Sampled: 10/04/05 10:30	Received	: 10/05/05	5 10:55					
Diesel	ND	10	mg/kg	1	CO07573	10/05/05	10/06/05	EPA 8015M	
MW-7-10.5' (COJ0127-05) Soil	Sampled: 10/04/05 12:15	Receive	d: 10/05/	05 10:55					
Diesel	ND	10	mg/kg	l	CO07573	10/05/05	10/06/05	EPA 8015M	
MW-7-15.5' (COJ0127-06) Soil	Sampled: 10/04/05 12:20	Receive	d: 10/05/	05 10:55					
Diesel	ND	10	mg/kg	1	CO07573	10/05/05	10/06/05	EPA 8015M	
MW-6-5.5' (COJ0127-07) Soil	Sampled: 10/04/05 14:25	Received	: 10/05/0	5 10:55					
Diesel	ND	5 0	mg/kg	5	CO07573	10/05/05	10/06/05	EPA 8015M	R-08
MW-6-10.5' (COJ0127-08) Soil	Sampled: 10/04/05 14:27	Receive	d: 10/05/6	05 10:55					
Diesel	ND	1 0	mg/kg	1	CO07573	10/05/05	10/06/05	EPA 8015M	
MW-6-15.5' (COJ0127-09) Soil	Sampled: 10/04/05 14:30	Receive	d: 10/05/0	05 10:55					
Diesel	ND	1 0	mg/kg	1	CO07573	10/05/05	10/06/05	EPA 8015M	

10/12/05 15:39

APEX Envirotech Inc - Gold River

11244 Pyrites Way Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: COJ0127

Project Number: RMA01 001

COC #: 56247

Project Manager: Rebekah Westrup

Extractable Petroleum Hydrocarbons by EPA Method 8015M

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
MW-6-23.5' (COJ0127-10) Soil	Sampled: 10/04/05 14:40	Receive	d: 10/05	05 10:55					
Diesel	ND	1 0	mg/kg	1	CO07573	10/05/05	10/06/05	EPA 8015M	

10/12/05 15:39

APEX Envirotech Inc - Gold River

11244 Pyrites Way Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: COJ0127

Project Number: RMA01 001 Project Manager: Rebekah Westrup COC#: 56247

Gas/BTEX by GC PID/FID

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
MW-5-6' (COJ0127-01) Soil	Sampled: 10/04/05 10:15	Received:	10/05/05	10:55					
Gasoline	ND	1000	μg/kg	1	CO07554	10/05/05	10/06/05	8015M/8021B	
Benzene	ND	5.0	n	н	U	a	H	¥	
Toluene	ND	5 0	н	11	D	D	н	D	
Ethylbenzene	ND	5 0	o o	U	н	Ħ	11	н	
Xylenes (total)	ND	10	0	P		н	0	N	
Surrogate: o-Chlorotoluene (Ga	s)	110%	65-	135	n	н	H	н	
MW-5-10.5' (COJ0127-02) Soi	l Sampled: 10/04/05 10:1	8 Receive	ed: 10/05/	05 10:55					
Gasoline	ND	1000	μg/kg	1	CO07554	10/05/05	10/06/05	8015M/8021B	
Benzene	ND	5 0	11	0	н	D	H	U	
Toluene	ND	5 0	n	ıt	11	н	U	Ħ	
Ethylbenzene	ND	5.0	н	N	H H	u	II	н	
Xylenes (total)	ND	10	II .	п	11		It .	11	
Surrogate. o-Chlorotoluene (Ga.	s)	110%	65-	13.5	н	n	н	n	
MW-5-15' (COJ0127-03) Soil	Sampled: 10/04/05 10:23	Received	: 10/05/05	5 10:55					
Gasoline	ND	1000	μg/kg	1	CO07554	10/05/05	10/06/05	8015M/8021B	
Benzene	ND	5 0	U	a	n	II .	н	11	
Toluene	ND	5.0	D	11	н	H	н	D	
Ethylbenzene	ND	5.0	н	н	U	•	11	H	
Xylenes (total)	ND	10	11	11	D	11	U	1	
Surrogate o-Chlorotoluene (Gas	5)	109 %	6.5-	135	v	н	,	н	
MW-5-23' (COJ0127-04) Soil	Sampled: 10/04/05 10:30	Received:	10/05/05	10:55					
Gasoline	ND	1000	μg/kg	1	CO07554	10/05/05	10/06/05	8015M/8021B	
Benzene	ND	5 0	"	И	1	н	11	ıı .	
l oluene	ND	5 0	п	n	U	1	U	H	
Ethylbenzene	ND	5 0	D	U	H	IJ	D	ř	
Kylenes (total)	ND	10	P	II .	11	D .	1	U	
Surrogate: o-Chlorotoluene (Gas	•)	112%	6.5-1	135	"	"	"	"	

10/12/05 15:39

APEX Envirotech Inc - Gold River

11244 Pyrites Way Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: CO J0127

Project Number: RMA01 001

Project Manager: Rebekah Westrup

COC #: 56247

Gas/BTEX by GC PID/FID

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
MW-7-10.5' (COJ0127-05) Soil	Sampled: 10/04/05 12:15	Receive	ed: 10/05	/05 10:55			· · ·		
Gasoline	ND	1000	μg/kg	1	CO07555	10/05/05	10/05/05	8015M/8021B	
Benzene	ND	5.0	н	0	ti	u	11	u	
Ioluene	ND	5 0	n	D	0	U	II.	n	
Ethylbenzene	ND	5 0	п	н	11	P†	D.	n,	
Xylenes (total)	ND	10		11	11	H	н		
Surrogate o-Chlorotoluene (Gas)		929%	65-	-13.5	н	н	u	Н	
MW-7-15.5' (COJ0127-06) Soil	Sampled: 10/04/05 12:20	Receive	ed: 10/05/	/05 10:55					
Gasoline	ND	1000	μg/kg	1	CO07555	10/05/05	10/05/05	8015M/8021B	
Benzene	ND	5 0	0	н	D	11	U	D	
Toluene	ND	5.0	n	a	н	Ħ	н	H	
Ethylbenzene	ND	50	н	"	11	"	Ħ	н	
Xylenes (total)	ND	10		H	0	,	"	(1	
Surrogate. o-Chlorotoluene (Gas)		94 3 %	65-	135	n	u	n	Н	
MW-6-5.5' (COJ0127-07) Soil	Sampled: 10/04/05 14:25	Received	: 10/05/0	5 10:55					
Gasoline	ND	1000	μg/kg	1	CO07555	10/05/05	10/05/05	8015M/8021B	
Benzene	ND	5 0	R	a	,	н	n	"	
Toluene	ND	5 0	11	n n	11	1	н	P	
Ethylbenzene	ND	5 0	0	н	n	U	п	н	
Xylenes (total)	ND	10	U	11	U	0	IJ	(1	
Surrogate o-Chlorotoluene (Gas)		947%	65-	135	n	u	n	n	
MW-6-10.5' (COJ0127-08) Soil	Sampled: 10/04/05 14:27	Receive	d: 10/05/	05 10:55					
Gasoline	ND	1000	μg/kg	1	CO07555	10/05/05	10/05/05	8015M/8021B	
Benzene	ND	5 0	11	U	Ħ	н	D	11	
Toluene	ND	5 0	п	"	п	11	м	н	
Ethylbenzene	ND	5.0	Ŋ	tt	II.	0	11	н	
Xylenes (total)	ND	10	Jt	II	H	II.	n	u	
Surrogate o-Chlorotoluene (Gas)		96 3 %	6.5	135	"	#	н	н	

10/12/05 15:39

APEX Envirotech Inc - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: COJ0127

11244 Pyrites Way Gold River, CA 95670

Project Number: RMA01 001 Project Manager: Rebekah Westrup

COC #: 56247

Gas/BTEX by GC PID/FID

Analyte	F Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
MW-6-15.5' (COJ0127-09) Soil	Sampled: 10/04/05 14:30	Receive	d: 10/05/	05 10:55					
Gasoline	ND	1000	μg/kg	1	CO07555	10/05/05	10/05/05	8015M/8021B	
Benzene	ND	5 0	"	*	н	17	Pt .	#1	
Toluene	ND	5 0	*1	†I	U	н	н	a	
Ethylbenzene	ND	5 0	11	n	IJ	U	a	D	
Xylenes (total)	ND	10		"	n	"		ır .	
Surrogate: o-Chlorotoluene (Gas)		969%	65	13.5	n	n	"	n	
MW-6-23.5' (COJ0127-10) Soil	Sampled: 10/04/05 14:40	Receive	d: 10/05/	05 10:55					
Gasoline	ND	1000	μg/kg	1	CO07555	10/05/05	10/05/05	8015M/8021B	
Benzene	ND	5 0	а	11	11	н	H	н	
l'oluene	ND	5 0	n	1	U	11	н	ti.	
Sthylbenzene	ND	5.0	11	U	D	U	(I	D	
Xylenes (total)	ND	10	#	H	н	n.	U	D	
Surrogate o-Chlorotoluene (Gas)		95.8%	65-7	'35	,,	"	,,	v	

10/12/05 15:39

APEX Envirotech Inc - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: COJ0127

11244 Pyrites Way Gold River, CA 95670 Project Number: RMA01 001

COC#: 56247

Project Manager: Rebekah Westrup

Non-halogenated Organic Compounds by EPA 8015

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
MW-5-6' (COJ0127-01) Soil	Sampled: 10/04/05 10:15	Received:	10/05/05	10:55					
Ethanol Methanol	ND ND	5.0 5.0	mg/kg	1	CO07622 н	10/07/05 "	10/07/05 "	EPA 8015B	
MW-5-10.5' (COJ0127-02) So	il Sampled: 10/04/05 10:1	8 Receive	ed: 10/05	05 10:55					
Ethanol Methanol	ND ND	5.0 5.0	mg/kg	1	CO07622 "	10/07/05	10/07/05	EPA 8015B	
MW-5-15' (COJ0127-03) Soil	Sampled: 10/04/05 10:23	Received	: 10/05/0:	5 10:55					
Ethanol Methanol	ND ND	5 0 5.0	mg/kg	1	CO07622	10/07/05	10/07/05	EPA 8015B	
MW-5-23' (COJ0127-04) Soil	Sampled: 10/04/05 10:30	Received	: 10/05/05	5 10:55					
Ethanol Methanol	ND ND	5.0 5.0	mg/kg	1	CO07622	10/07/05	10/07/05	EPA 8015B	
MW-7-10.5' (COJ0127-05) So	il Sampled: 10/04/05 12:1	5 Receive	d: 10/05/	05 10:55					
Ethanol Methanol	ND ND	5.0 5.0	mg/kg	1	CO07622	10/07/05	10/07/05	EPA 8015B	
MW-7-15.5' (COJ0127-06) Soi	l Sampled: 10/04/05 12:2	0 Receive	d: 10/05/	05 10:55					
Ethanol Methanol	ND ND	5 0 5 0	mg/kg	1 "	CO07622	10/07/05	10/07/05	EPA 8015B	
MW-6-5.5' (COJ0127-07) Soil	Sampled: 10/04/05 14:25	Received	: 10/05/0	5 10:55					
Ethanol Methanol	ND ND	5.0 5.0	mg/kg	1	CO07622	10/07/05	10/07/05	EPA 8015B	

10/12/05 15:39

APEX Envirotech Inc - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: COJ0127

11244 Pyrites Way Gold River, CA 95670

Project Number: RMA01 001 Project Manager: Rebekah Westrup

COC #: 56247

Non-halogenated Organic Compounds by EPA 8015

Analyte	Result	eporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
MW-6-10.5' (COJ0127-08) Soil	Sampled: 10/04/05 14:27	Receive	d: 10/05	05 10:55					
Ethanol Methanol	ND ND	5 0 5 0	mg/kg	1	CO07622	10/07/05	10/07/05	EPA 8015B	•
MW-6-15.5' (COJ0127-09) Soil	Sampled: 10/04/05 14:30		:d: 10/05/	05 10:55					
Ethanol Methanol	ND ND	5 0 5 0	mg/kg	1	CO07622	10/07/05	10/07/05	EPA 8015B	
MW-6-23.5' (COJ0127-10) Soil	Sampled: 10/04/05 14:40	Receive	d: 10/05/	05 10:55					
Ethanol Methanol	ND ND	5 0 5 0	mg/kg	1	CO07622	10/07/05	10/07/05	EPA 8015B	

10/12/05 15:39

APEX Envirotech Inc - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: COJ0127

11244 Pyrites Way Gold River, CA 95670

Project Number: RMA01.001 Project Manager: Rebekah Westrup

COC #: 56247

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Anaîyzed	Method	Note
MW-5-6' (COJ0127-01) Soil	Sampled: 10/04/05 10:15	Received:	10/05/05	10:55					
Di-isopropyl ether	ND	5 0	μg/kg	1	CO07653	10/07/05	10/10/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5 0	н	н	н	Ħ	11	Ħ	
Methyl tert-butyl ether	ND	5.0	я	11	11	u	п	ű	
tert-Amyl methyl ether	ND	5 0	U	II .	U	II .	n	U	
Ter t-butyl alcohol	1300	50	17	"	н	11	*	11	
1,2-Dibromoethane (EDB)	ND	5.0	п	н	н	11	a	н	
1,2-Dichloroethane	ND	5.0	U	11	•	u	11	11	
Surrogate Toluene-d8		998%	60-	140	н	"	"	"	
MW-5-10.5' (COJ0127-02) So	oil Sampled: 10/04/05 10:	18 Receive	ed: 10/05/	05 10:55					
Di-isopropyl ether	ND	5 0	μg/kg	1	CO07653	10/07/05	10/10/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5 0	19	n,	D.	n	11	U	
Methyl tert-butyl ether	ND	5.0	н	N	н	И	H	n	
tert-Amyl methyl ether	ND	5 0	U	11	11	II .	ıı .	п	
Tert-butyl alcohol	10000	500	11	10	If	H	11	u	
1,2-Dibromoethane (EDB)	ND	5.0	Ħ	1	n	H	н	U	
1,2-Dichloroethane	ND	5.0	11	н	н	11	14	н	
Surrogate Toluene-d8		99 4 %	60-	140	n	"	"	"	
MW-5-15' (COJ0127-03) Soil	Sampled: 10/04/05 10:23	Received	: 10/05/05	10:55					
Di-isopropyl ether	ND	5 0	μg/kg	1	CO07653	10/07/05	10/10/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5.0	н	11	11	"	ır	U	
Methyl tert-butyl ether	ND	5 0	u	11	Ħ	Œ	н	11	
tert-Amyl methyl ether	ND	5 0		U	o o	U	u	н	
Tert-butyl alcohol	6400	200	It	4	H	н	D	u	
1,2-Dibromoethane (EDB)	ND	5 0	11	1	H	н	М	u	
1,2-Dichloroethane	ND	5.0	10	u	н	11	11	ıt	
Surrogate Toluene-d8		976%	60-,	140	11	"	ų	"	

10/12/05 15:39

APEX Envirotech Inc - Gold River

11244 Pyrites Way

Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: CO J0127

Project Number: RMA01 001

Project Manager: Rebekah Westrup

COC #: 56247

Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Notes
MW-5-23' (COJ0127-04) Soil	Sampled: 10/04/05 10:30	Received	l: 10/05/05	5 10:55					
Di-isopropyl ether	ND	5.0	μg/kg	1	CO07653	10/07/05	10/10/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5 0	J	U	a	t	М	U	
Methyl tert-butyl ether	860	25	11	5	н	11	Ð	D	
tert-Amyl methyl ether	ND	5.0	н	1	17		ø	И	
I ert-butyl alcohol	420	50	er er	n	J	#1	11	,	
1,2-Dibromoethane (EDB)	ND	5 0	0	"	11	'n	n	11	
1,2-Dichloroethane	ND ND	5.0	11	н	n	11	н	n	
Surrogate Toluene-d8		976%	60-	140	n	н	и	"	
MW-7-10.5' (COJ0127-05) Soil	Sampled: 10/04/05 12:15	5 Receive	ed: 10/05/	05 10:55					
Di-isopropyl ether	ND	5.0	μg/kg	1	CO07653	10/07/05	10/10/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5 0	O .	IJ	ti	н	If	R	
Methyl tert-butyl ether	ND	5 0	11	P	п	Ħ	n	q	
tert-Amyl methyl ether	ND	5.0	TI TI	a	17	II	*1	0	
Tert-butyl alcohol	ND	50	U	0	11	lt .	o	R	
1,2-Dibromoethane (EDB)	ND	5 0	17	17	IJ	И	17	н	
1,2-Dichloroethane	ND	5.0	н	fl	D	u	н	9	
Surrogate Toluene-d8		960%	60-1	140	"	"	n	"	
MW-7-15.5' (COJ0127-06) Soil	Sampled: 10/04/05 12:20	Receive	d: 10/05/0)5 10:55					
Di-isopropyl ether	ND	5 0	μg/kg	1	CO07653	10/07/05	10/10/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5.0	10		U	N	"	н	
Methyl tert-butyl ether	ND	5 0	11	11	n	11	и	11	
tert-Amyl methyl ether	ND	5 0	U	U	н	U	ti .		
Tert-butyl alcohol	ND	50	0	11	u	B	ø	U	
1,2-Dibromoethane (EDB)	ND	5 0	n	И	11	н		n	
1,2-Dichloroethane	ND	5.0	11	п	11	(1	н	н	
Surrogate Toluene-d8		988%	60-1	40	n	n	"	n	

10/12/05 15:39

APEX Envirotech Inc. - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: COJ0127

Project Number: RMA01 001

COC #: 56247

11244 Pyrites Way Gold River, CA 95670

Project Manager: Rebekah Westrup

	77 TO 20								
Analyte	Result	Reporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
MW-6-5.5' (COJ0127-07) Soil	Sampled: 10/04/05 14:25	Received	1: 10/05/0	5 10:55			_		
Di-isopropyl ether	ND	5 0	μg/kg	1	CO07653	10/07/05	10/10/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5.0	и	l+	0	u	н	If	
Methyl tert-butyl ether	ND	5.0	0	н	II.	IJ	и	n	
tert-Amyl methyl ether	ND	5 0	0	11	It.	11	11	п	
Tert-butyl alcohol	ND	50	If	U	**	n	U	u	
1,2-Dibromoethane (EDB)	ND	5 0	Ħ	17	a	u	11	II .	
1,2-Dichloroethane	ND	5.0		H	11	U	н	11	
Surrogate Toluene-d8		96.6%	60-1	140	"	"	v	n	
MW-6-10.5' (COJ0127-08) Soil	Sampled: 10/04/05 14:27	Receive	d: 10/05/0	5 10:55					
Di-isopropyl ether	ND	5 0	μg/kg	l	CO07653	10/07/05	10/10/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5 0	F	11	11	11	U	v	
Methyl tert-butyl ether	ND	5.0	U	н	U	"	11	II .	
tert-Amyl methyl ether	ND	5 0	D	н	11	"	н	D	
Tert-butyl alcohol	ND	50	н		11	H	ĮI.	н	
1,2-Dibromoethane (EDB)	ND	5 0	и	U	11	н	11	н	
1,2-Dichloroethane	ND	5.0	11	lt .	· ·	я	9	11	
Surrogate Toluene-d8		100 %	60-1	40	"	"	н	n	
MW-6-15.5' (COJ0127-09) Soil	Sampled: 10/04/05 14:30	Receive	d: 10/05/0	5 10:55					
Di-isopropyl ether	ND	5.0	μg/kg	1	CO07653	10/07/05	10/10/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5.0	0	М	U	n	U.	11	
Methyl tert-butyl ether	ND	5 0	0	11	D.	1)	"	U	
tert-Amyl methyl ether	ND	5 0	н	U	ìτ	11	н	1)	
Tert-butyl alcohol	ND	50	н	D	11	H	н	It.	
1,2-Dibromoethane (EDB)	ND	5.0	u	If	o o	a	u	Ħ	
1,2-Dichloroethane	ND	5.0	0	"	II .	U	U	11	
Surrogate Toluene-d8		102 %	60-1	40	n	и	"	н	

10/12/05 15:39

APEX Envirotech Inc - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: COJ0127

11244 Pyrites Way Gold River, CA 95670

Project Number: RMA01.001 Project Manager: Rebekah Westrup

COC #: 56247

Analyte	R Result	eporting Limit	Units	Dilution	Batch	Prepared	Analyzed	Method	Note
MW-6-23.5' (COJ0127-10) Soil	Sampled: 10/04/05 14:40	Receive	d: 10/05/	05 10:55					
Di-isopropyl ether	ND	5 0	μg/kg	ı	CO07664	10/10/05	10/10/05	EPA 8260B	
Ethyl tert-butyl ether	ND	5 0	н	11	U	n		n	
Methyl tert-butyl ether	ND	5.0	н	н	#	11	D.	н	
tert-Amyl methyl ether	ND	5 0	u	11	t.	н	н	п	
Tert-butyl alcohol	ND	50		U	ø	a		1	
1,2-Dibromoethane (EDB)	ND	5 0	H	D	n	"	U	D	
1,2-Dichloroethane	ND	5 0	11	н	n	It	D	D.	
Surrogate Toluene-d8		101 %	60-	140	,,	u	п	v	

10/12/05 15:39

APEX Envirotech Inc. - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: COJ0127

11244 Pyrites Way Gold River, CA 95670

Project Number: RMA01.001 Project Manager: Rebekah Westrup

COC #: 56247

Extractable Petroleum Hydrocarbons by EPA Method 8015M - Quality Control

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch CO07573 - LUFI-DHS GCNV										
Blank (CO07573-BLK1)				Prepared:	10/05/05	Analyzed	: 10/06/05			
Diesel	ND	10	mg/kg	•						
LCS (CO07573-BS1)				Prepared:	10/05/05	Analyzed	10/06/05			
Diesel	50.3	10	mg/kg	50 0		101	65-135			
LCS Dup (CO07573-BSD1)				Prepared:	10/05/05	Analyzed	: 10/06/05			
Diesel	47 7	10	mg/kg	50 0		95 4	65-135	5 3 1	30	
Matrix Spike (CO07573-MS1)	So	urce: COJ01	27-10	Prepared:	10/05/05	Analyzed	: 10/06/05			
Diesel	48 9	1 0	mg/kg	50.0	ND	97.8	59-138			
Matrix Spike Dup (CO07573-MSD1)	So	urce: COJ01	27-10	Prepared:	10/05/05	Analyzed	: 10/06/05			
Diesel	50.4	10	mg/kg	50 0	ND	101	59-138	3 02	37	

10/12/05 15:39

APEX Envirotech Inc - Gold River

11244 Pyrites Way Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: COJ0127

Project Number: RMA01 001 Project Manager: Rebekah Westrup

COC #: 56247

Gas/BTEX by GC PID/FID - Quality Control

Analyte	Dogult	Reporting Limit	Y Touris	Spike	Source	0/7070	%REC	DDD	RPD	.,
Allaryte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch CO07554 - EPA 5030 Soil GC										
Blank (CO07554-BLK1)				Prepared	& Analyze	ed: 10/05/	05			
Gasoline	ND	1000	μg/kg							
Benzene	ND	5 0	U							
Toluene	ND	5 0	11							
Ethylbenzene	ND	5.0	11							
Xylenes (total)	ND	10	Ü							
Surrogate o-Chlorotoluene (BTEX)	122		"	100		122	65-135			
Surrogate o-Chlorotoluene (Gas)	112		H	100		112	65-135			
LCS (CO07554-BS1)				Prepared	& Analyze	d: 10/05/	05			
Gasoline	2120	1000	μg/kg	2500		84 8	65-135			
Surrogate o-Chlorotoluene (Gas)	107		"	100		107	65-135			
LCS Dup (CO07554-BSD1)				Prepared a	& Analyze	d: 10/05/	05			
Gasoline	2310	1000	μg/kg	2500		92 4	65-135	8 58	30	
Surrogate o-Chlorotoluene (Gas)	114		"	100		114	6.5-13.5			
Matrix Spike (CO07554-MS1)	Sou	rce: COJ000	69-08	Prepared of	& Analyze	d: 10/05/0	05			
Gasoline	2390	1000	μg/kg	2500	ND	95 6	63-124			***
Surrogate o-Chlorotoluene (Gas)	114		н	100		114	65-135			
Matrix Spike Dup (CO07554-MSD1)	Sou	rce: COJ000	59-08	Prepared &	& Analyze	d: 10/05/0)5			
Gasoline	2430	1000	μg/kg	2500	ND	97 2	63-124	1 66	35	
Batch CO07555 - EPA 5030 Soil GC										
Blank (CO07555-BLK1)				Prepared &	& Analyze	d: 10/05/0)5			
Gasoline	ND	1000	μg/kg		y					
Зеплене	ND	50	"							
oluene	ND	5.0	**							
Ethylbenzene	ND	50	п							
Kylenes (total)	ND	10	11							
urrogate o-Chlorotoluene (BTEX)	109		u	100		109	65-135			

10/12/05 15:39

APEX Envirotech Inc - Gold River

11244 Pyrites Way Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: COJ0127

Project Number: RMA01 001

COC #: 56247

Project Manager: Rebekah Westrup

Gas/BTEX by GC PID/FID - Quality Control

	Reporting			Spike	Source		%REC		RPD	
Analyte	Result	Limit	Units	Level	Result	%REC	Limits	RPD	Limit	Notes
Batch CO07555 - EPA 5030 Soil GC	No. 1									
Blank (CO07555-BLK1)				Prepared	& Analyzo	ed: 10/05/	05			
Surrogate: o-Chlorotoluene (Gas)	98 6		μg/kg	100		98 6	6.5-1.3.5			
LCS (CO07555-BS1)				Prepared	& Analyze	ed: 10/05/	05			
Gasoline	2050	1000	μg/kg	2500		82 0	65-135			
Surrogate o-Chlorotoluene (Gas)	103		n	100	,	103	6.5-13.5			
LCS Dup (CO07555-BSD1)				Prepared a	& Analyze	ed: 10/05/	05			
Gasoline	2390	1000	μg/kg	2500		95.6	65-135	15 3	30	
Surrogate. o-Chlorotoluene (Gas)	104		"	100		104	65-135			
Matrix Spike (CO07555-MS1)	Sou	ırce: COJ00	69-12	Prepared & Analyzed: 10/05/05						
Gasoline	2290	1000	μg/kg	2500	ND	916	63-124			
Surrogate o-Chlorotoluene (Gas)	97 3		"	100		97 3	65-135			
Matrix Spike Dup (CO07555-MSD1)	Sou	rce: COJ00	69-12	Prepared a	& Analyze	d: 10/05/0	05			
Gasoline	1970	1000	μg/kg	2500	ND	78 8	63-124	15.0	35	
Surrogate o-Chlorotoluene (Gas)	101		"	100	•	101	65-135	· ··- ··-		

10/12/05 15:39

APEX Envirotech Inc - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: CO J0127

Project Number: RMA01 001

COC #: 56247

11244 Pyrites Way Gold River, CA 95670

Project Manager: Rebekah Westrup

Non-halogenated Organic Compounds by EPA 8015 - Quality Control

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
Batch CO07622 - LUFT-DHS GCNV										
Blank (CO07622-BLK1)				Prepared	& Analyz	ed: 10/07/	05			
Ethanol	ND	5 0	mg/kg				•			
Methanol	ND	5 0	II							
LCS (CO07622-BS1)				Prepared	& Analyz	ed: 10/07/	05			
Methanol	517	5 0	mg/kg	50 0		103	75-125			
LCS Dup (CO07622-BSD1)				Prepared	& Analyz	ed: 10/07/	05			
Methanol	49.1	5 0	mg/kg	50.0		98 2	75-125	5 16	30	
Matrix Spike (CO07622-MS1)	So	urce: COJ01	27-01	Prepared a	& Analyz	ed: 10/07/	05			
Methanol	27 1	5.0	mg/kg	50 0	ND	54 2	75-125			QM-01
Matrix Spike Dup (CO07622-MSD1)	So	arce: COJ01	27-01	Prepared a	& Analyz	ed: 10/07/0	05			
Methanol	32 0	5.0	mg/kg	50 0	ND	64 0	75-125	166	30	QM-01

10/12/05 15:39

APEX Envirotech Inc. - Gold River

11244 Pyrites Way

Gold River, CA 95670

Project: Rotten Robbie Service Station CLS Work Order #: COJ0127

Project Number: RMA01 001 Project Manager: Rebekah Westrup

COC #: 56247

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
<u></u>	Result	Link	Olitis	Level	Kesun	70KEC	Linus	KrD	Lillit	Notes
Batch CO07653 - EPA 5030 Soil MS										
Blank (CO07653-BLK1)				Prepared:	10/07/05	Analyzed	1: 10/10/05			
Di-isopropyl ether	ND	5 0	μg/kg				•			
Ethyl tert-butyl ether	ND	50	u							
Methyl tert-butyl ether	ND	5 0	11							
tert-Amyl methyl ether	ND	5 0	n							
Tert-butyl alcohol	ND	50	11							
1,2-Dibromoethane (EDB)	ND	5 0	I†							
1,2-Dichloroethane	ND	5 0	n							
Surrogate Toluene-d8	48 9	-	n	50 0		978	60-140			
LCS (CO07653-BS1)				Prepared:	10/07/05	Analyzed	: 10/10/05			
Methyl tert-butyl ether	45 7	5 0	μg/kg	50.0		91.4	60-140		- 10	
Surrogate Toluene-d8	50 2		"	50 0		100	60-140			
LCS Dup (CO07653-BSD1)				Prepared:	10/07/05	Analyzed	: 10/10/05			
Methyl tert-butyl ether	39 3	5 0	μg/kg	50.0		78.6	60-140	15 1	30	
Surrogate Toluene-d8	49 3		и	50 0		98 6	60-140			
Matrix Spike (CO07653-MS1)	Sou	rce: COJ01	48-05	Prepared:	10/07/05	Analyzed	: 10/10/05			
Methyl tert-butyl ether	40 8	50	μg/kg	50.0	ND	81.6	60-140			
Surrogate. Toluene-d8	48 8		"	50 0		97 6	60-140			
Matrix Spike Dup (CO07653-MSD1)	Sou	rce: COJ014	48-05	Prepared:	10/07/05	Analyzed	: 10/10/05			
Methyl tert-butyl ether	39.1	5 0	μg/kg	50 0	ND	78 2	60-140	4 26	30	
Surrogate Toluene-d8	50 2		"	.50 0		100	60-140			
Batch CO07664 - EPA 5030 Soil MS										
Blank (CO07664-BLK1)				Prepared &	& Analyz	ed: 10/10/0)5			
Di-isopropyl ether	ND	5 0	μg/kg	F C V	, 20		-			
Ethyl tert-butyl ether	ND	5 0	#							
Methyl tert-butyl ether	ND	5.0	Ħ							
ert-Amyl methyl ether	ND	5 0	ıı.							

10/12/05 15:39

APEX Envirotech Inc. - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: COJ0127

11244 Pyrites Way Gold River, CA 95670

Project Manager: Rebekah Westrup

Project Number: RMA01 001

COC #: 56247

Analyte	Result	Reporting Limit	Units	Spike Level	Source Result	%REC	%REC Limits	RPD	RPD Limit	Notes
	TOSHIT	Lillit	Omis	LUYUI	ivoant	/urcic	Laints	МЪ	Linit	INGIES
Batch CO07664 - EPA 5030 Soil MS										
Blank (CO07664-BLK1)				Prepared	& Analyze	ed: 10/10/	05			
Tert-butyl alcohol	ND	50	μg/kg							
Surrogate Toluene-d8	49 4		n	50 0		988	60-140			
LCS (CO07664-BS1)				Prepared	& Analyze	ed: 10/10/	05			
Methyl tert-butyl ether	42 2	5 0	μg/kg	50 0		84 4	60-140	· · · · ·		
Surrogate Toluene-d8	50 1		"	50 0		100	60-140			
LCS Dup (CO07664-BSD1)				Prepared a	& Analyze	d: 10/10/	05			
Methyl tert-butyl ether	36 8	5 0	μg/kg	50 0		73 6	60-140	13 7	30	
Surrogate Toluene-d8	50 7		"	50 0		101	60-140		,	
Matrix Spike (CO07664-MS1)	So	urce: COJ01	Prepared a							
Methyl tert-butyl ether	45 1	5 0	μg/kg	50 0	ND	90 2	60-140			
Surrogate Toluene-d8	51 1		"	50 0		102	60-140			
Matrix Spike Dup (CO07664-MSD1)	So	urce: COJ01	27-10	Prepared &	& Analyze	d: 10/10/0)5			
Methyl tert-butyl ether	49 5	5 0	μg/kg	50.0	ND	99 0	60-140	9 30	30	•
Surrogate Toluene-d8	51 2	*****	"	50 0		102	60-140			

10/12/05 15:39

APEX Envirotech Inc. - Gold River

Project: Rotten Robbie Service Station CLS Work Order #: COJ0127

11244 Pyrites Way Gold River, CA 95670

Project Number: RMA01.001 Project Manager: Rebekah Westrup

COC #: 56247

Notes and Definitions

R-08 The extract of this sample was dark and/or oily Therefore, the sample was analyzed with a dilution and the reporting limit was

raised for all target compounds

The spike recovery for this QC sample is outside of established control limits due to sample matrix interference QM-01

DEI Analyte DETECTED

ND Analyte NOT DETECTED at or above the reporting limit

NR Not Reported

Sample results reported on a dry weight basis dry

RPD Relative Percent Difference